

CORONADO PAINT CO, INC. -- RUBBER BASE MASONRY PAINT, BLUE -- 8010-00-054-9325

=====  
Product Identification  
=====

Product ID:RUBBER BASE MASONRY PAINT, BLUE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-054-9325

MSDS Number: BCWJG

=== Responsible Party ===

Company Name:CORONADO PAINT CO, INC.

Emergency Phone Num:904 428-6461

CAGE:33200

=== Contractor Identification ===

Company Name:CORONADO PAINT COMPANY  
, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====  
Composition/Information on Ingredients  
=====

Ingred Name:AROMATIC AND ALIPHATIC HYDROCARBONS

RTECS #:ZE2190000

Fraction by Wt: 48.1%

ACGIH TLV:200 PPM

Ingred Name:VEHICLE

Fraction by Wt: 20.2%

ACGIH TLV:NO HAZARD

Ingred Name:PIGMENTS

Fraction by Wt: 31.7%

ACGIH TLV:NO HAZARD

=====  
Hazards Identification  
=====

Effect

s of Overexposure: DRYING OF SKIN. EYE IRRITATION. EXCESSIVE INHALATION MAY CAUSE HEADACHE AND NAUSEA.

=====  
First Aid Measures  
=====

First Aid: INHALATION: REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION IF NECESSARY, CALL A PHYSICIAN. SKIN CONTACT: WASH WITH MILD SOAP & WATER, APPLY A MILD SKIN CREAM, IN SEVERE CASES, CONTACT A PHYSICIAN. EYE CONTACT: FLUSH WITH WATER .

=====  
Fire Fighting Measures  
=====

Flash Point: 65F SETA

Lower Limits: 0.9

Upper Limits: 7.0

Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures: TREAT AS CLASS B FIRE

Unusual Fire/Explosion Hazard: VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR.

=====  
Accidental Release Measures  
=====

Spill Release Procedures: FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER. AVOID SPARKS, FIRE, OR HOT METAL SURFACES. SMALL QUANTITIES MAY BE ABSORBED ONTO AN APPROPRIATE ABSORBANT.

=

=====  
Handling and Storage  
=====

Handling and Storage Precautions: KEEP COOL & AWAY FROM SOURCES OF IGNITION. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED PERSONAL CONTACT.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection: DEPENDS ON CONCENTRATION ABOVE TIME WEIGHTED TLV-OR GAS MASK.

Ventilation: SUFFICIENT TO MAINTAIN WORKROOM ATMOSPHERE BELOW TLV.

Protective Gloves: IMPERMEABLE

Eye Protection: CHE

MICAL GOGGLES

Other Protective Equipment: APRON, BARRIER CREME.

Supplemental Safety and Health

CORONADO PAINT CO, INC. 308 OLD COUNTY ROAD; EDGEWATER, FLA. 32032

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:240F

Vapor Pres:6

Vapor Density:3.7

Spec Gravity:1.18

Evaporation Rate & Reference:0.9

Solubility in Water:VERY SLIGHT

Appearance and Odor:LIGHT BLUE OPAQUE LIQUID. PETROLEUM ODOR.

Percent Volatiles by Volume:67

===== Stab

ility and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES, FIRE.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE & DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer

(provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.