Product ID:23F1220 MSDS Date:01/01/1985

FSC:5910

NIIN:00-072-0066

MSDS Number: BCXJM === Responsible Party ===

Company Name: GENERAL ELECTRIC CORP. CAPACITOR PROD. DEPT.

Address:JOHN ST City:HUDSON FALLS

State:NY ZIP:12839 Country:US

Emergency Phone Num:800-626-2000

CAGE:01002 === Contract

or Identification ===

Company Name: GENERAL ELECTRIC CO CAPACITOR PRODUCTS DEPARTMENT

Address: JOHN ST

Box:City:HUDSON FALLS

State:NY ZIP:12839 Country:US

Phone:518-746-5750

CAGE:01002

======= Composition/Information on Ingredients ========

Ingred Name: POLYCHLORINATED BIPHENYLS (PCBS) (SARA III)

CAS:1336-36-3

RTECS #:TQ1350000 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

============= Hazards Identification ========================

Effects of Overexposure: ABSORBED THRU SKIN, LUNGS, INT

CANCER, LIVER, KIDNEY, STOMACH, EYE, HEARING DISORDER (SUP DATA)
======================================
First Aid:EYES:FLUSH W/WATER IMMEDIATELY.SKIN:WASH W/SOAP IMMED.INHAL:REMOVE TO FRESH AIR,GIVE ART.RESPIR.AS NEEDED.INGEST:GET MEDICAL ATTN.GIVE LARGE QTY OF SALT WATER,INDUCE VOMITING,BUT DO NOT MAKE UNCONSCIO US PERSON VOMIT.
======== Accidental Release Measures =========
Spill Release Procedures:USE ABSORBENT & D IKES TO PREVENT
RUNOFF.ISOLATE & NOTIFY PROPER AUTHORITIES.
=========== Handling and Storage ============
Handling and Storage Precautions:STORAGE MUST FOLLOW RCRA REQUIREMENTS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:SUPPLIED AIR W/FULL FACEPIECE,HELMET OR HOOD Ventilation:LOCAL EXHAUST Protective Gloves:RUBBER-IMPERV Eye Protection:GOGGLES,FACE SHIELD Other Protective Equipment:FULL CLOTHING TO PREVENT SKIN CONTAC T
Supplemental Safety and Health OVEREXPOS:MAY CAUSE FORMATION OF CYSTS, CAUSES STILLBIRTHS. IRRITATES EYES, NOSE THROAT
======== Physical/Chemical Properties =========
HCC:Z3 Appearance and Odor:LIGHT STRAW-COLORED LIQUID,AROMATIC ODOR
======== Stability and Reactivity Data =========
STRONG OXIDIZERS
======= Disposal Considerations ===========
Waste Disposal Methods:CONTROLLED DISPOSAL REQUIRED-GENERALLY HIGH TEMPERATURE

ESTINE.CAUSES

INCINERATION.ONLY APPROVED DISPOSAL OPERATOR PERMITTED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the su itability of this information to their particular situation.