

UNION CARBIDE CORPORATION -- UCON PROPELLANT 11 -- 6830-00-079-4694

=====  
Product Identification  
=====

Product ID:UCON PROPELLANT 11

MSDS Date:01/01/1985

FSC:6830

NIIN:00-079-4694

MSDS Number: BCXRS

=== Responsible Party ===

Company Name:UNION CARBIDE CORPORATION

Emergency Phone Num:212-551-4785

CAGE:6M841

=== Contractor Identification ===

Company Name:UNION CARBIDE CORP

Address:OLD RIDGEBURY RD

B

City:DANBURY

State:CT

ZIP:06817

Country:US

CAGE:6M841

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TRICHLOROFLUOROMETHANE (CFC-11) (SARA III)

CAS:75-69-4

RTECS #:PB6125000

Fraction by Wt: 100%

OSHA PEL:1000 PPM

ACGIH TLV:C, 1000 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

=====  
Hazards Identification  
=====

Effects of Overexposure:FROSTBITE.BREATHING CONCENTRATIONS APPROACHING  
10%

IN AIR WILL CAUSE DIZZINESS & DROWSINESS

=====  
First Aid Measures  
=====

First Aid:FLUSH FROSTED AREAS WITH WARM WATER.IF INHALED IN HIGH CONCENTRATIONS, MOVE TO FRESH AIR

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:COVER WITH ABSORBENT MATERIAL(& LOAD INTO WASTE CONTAINER

=====  
Handling and Storage  
=====

Handling and Storage Precautions:CAUTION! LIQUID & GAS UNDER PRESSURE.KEEP AWAY FROM HEAT AND OPEN FLAMES.DO NOT DROP OR REFILL.NON FLAMMABLE LIQUID GAS

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:FRESH-AIR MASK FOR HIGH CONCENTRATIONS  
Ventilation:LOCAL EXHAUST IS PREFERRED.MECHANICAL IS ACCEPTABLE  
Eye Protection:SAFETY GLASSES  
Other Protective  
Equipment:EYE BATH & SAFETY SHOWER  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:N1  
Boiling Pt:B.P. Text:74.8F  
Vapor Pres:13  
Vapor Density:4.7  
Spec Gravity:1.49  
Evaporation Rate & Reference:63 BUTYL ACETATE  
Solubility in Water:0.11%  
Appearance and Odor:WATER-WHITE LIQUID;CHLORINATED SOLVENT ODOR  
Percent Volatiles by Volume:100

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoi

d:YES

NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:HCL,HF,CO,AND/OR CO\*2

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL OR MIX IN SMALL PROPORTION WITH  
BURNABLE LIQUID & INCINERATE UNDER APPROVED CONTROLLED PROCEDURES

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no man

er whatsoever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.