

CLAYTON CHEMICAL CO. -- 209-061 INDUSTRIAL X-RAY HARDENER, PART B -- 6750-00-092-5054
===== Product Identification =====

Product ID:209-061 INDUSTRIAL X-RAY HARDENER, PART B

MSDS Date:06/11/1988

FSC:6750

NIIN:00-092-5054

MSDS Number: BCYMM

=== Responsible Party ===

Company Name:CLAYTON CHEMICAL CO.

Address:13310 FIGUEROA STREET

City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Info Phone Num:213-538-
9530

Emergency Phone Num:213-538-9530

CAGE:61803

=== Contractor Identification ===

Company Name:CLAYTON CHEMICAL CO.

Address:13310 S. FIGUEROA STREET

Box:City:LOS ANGELES

State:CA

ZIP:90061

Country:US

Phone:310-538-9530/800-424-9300(CHEMTREC)

CAGE:61803

===== Composition/Information on Ingredients =====

Ingred Name:ALUMINUM SULFATE (SARA III)

CAS:10043-01-3

RTECS #:BD1700000

Fraction by Wt: 35%

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LB

S

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: BAL

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INHALATION OF VAPORS OR MIST MAY
RESULT IN BRONCHITIS,PULMONARY EDEMA & CHEMICAL PNEUMONITIS;
INGESTION OF LIQUID WILL BURN MOUTH & THROAT CAUSING SEVERE
ABDOMINAL PAIN,NAUSEA,VOMITING & COLLAPSE.
Effects of Overexposure:INHALATION: VAPORS CAN CAUSE
COUGHING,CHOKING,AND IRRITATION OF THE RESPIRATORY TRACT.
INGESTION: CAN CAUSE IRRITATION TO MOUTH & GI TRACT. EYE/SKIN: CAN
CAUSE SEVERE IRRITATION TO EYES AND SKIN. MIS T OR LIQUID CONTACT
MAY DAMAGE THE EYESPERMANENTLY.IN SEVERE CONDITIONS OF
OVEREXPOSURE,VAPORS MAY CAUSE BURNS TO EYES.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR RESPIRATORY
TRACT PROBLEMS MAY BE MORE SUSCEPTIBLE TO THE
EFFECTS OF THIS
PRODUCT

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.RESUSCITATE IF NOT
BREATHING.GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY
OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN.GET MEDICAL ATTENTION.
SKIN:REMOVE CO NTAMINATED CLOTHING. WASH WITH PLENTY OF WATER FOR
15 MINUTES.GET MEDICAL ADVICE. INGESTION:GIVE MILK OR WATER.DO NOT
INDUCE VOMITING.GIVE NOTHING BY MOUTH IF UNCONSCIOUS
. GET IMMEDIATE
MEDICAL HELP.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE APPROPRIATE MEDIA FOR SURROUNDING FIRES.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:NONE NONE TO CLAYTON.

===== Accidental Release Measures =====

=

Spill Release Procedures:ABSORB & REMOVE BULK OF SPILL WITH ABSORBENT SWEEPING COMPOUND,NEUTRALIZE ANY REMAINING LIQUID WITH A SUITABLE BASE SUCH AS SODIUM HYDROXIDE.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING FUMES. WEAR APPROPRIATE PROTECTIVE CLOTHING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED USUALLY.
Ventilation:LOCAL EXHAUST
Protective G
loves:RUBBER/NEOPRENE
Eye Protection:CHEMICAL SPLASH GOGGLES
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
THIS IS PART-B OF A TWO (2) PARTS KIT.PART A IS UNDER PNI "A",THIS
NSN.KEY1:C1

===== Physical/Chemical Properties =====
=====

HCC:C1
Boiling Pt:B.P. Text:>212F/100C
Spec Gravity:1.24
pH:1.8
Evaporation Rate & Reference: