

SEYMOUR OF SYCAMORE INC -- GP-0001-1670,RED -- 8010-00-141-2952

=====
Product Identification
=====

Product ID:GP-0001-1670,RED

MSDS Date:05/20/1993

FSC:8010

NIIN:00-141-2952

MSDS Number: BDBNP

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE INC

Address:917 CROSBY AVE

City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Info Phone Num:815-892-9101

Emergency Phone Num:815-891-9101

CAGE:59581

=== Contractor Identification ===

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

=====
Composition/Information on Ingredients
=====

Ingred Name:TITANIUM DIOXIDE, TIO2

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 5.28%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:DICHLOROMETHANE (METHYLENE CHLORIDE) (SUSPECTED HUMAN
CARCINOGEN BY ACGIH, NTP)

CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 21.83%
OSHA PEL:500 PPM
ACGIH TLV:174 MG/CUM (A2)
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 1.45%
Other REC Limits:1900 MG/CUM
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

Ingred Name:XYLENE, DIMETHYLBENZENE, XYLOL
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 1.47%
Other REC Limits:100 PPM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM, SKIN
EPA Rpt Qty:1000 LBS
DOT
Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 0.37%
Other REC Limits:100 PPM
OSHA PEL:435 MG/CUM
ACGIH TLV:434 MG/CUM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:EPOXYPROPANE, PROPYLENE OXIDE
CAS:75-56-9
RTECS #:TZ2975000
Fraction by Wt: 0.11%
Other REC Limits:20 PPM
OSHA PEL:100 PPM
ACGIH TLV:20 PPM; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 17.75%
Other REC Limits:375

MG/CUM
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:KEROSENE (PETROLEUM), HYDROTREATED; PETROLEUM DISTILLATE,
HYDROTREATED
CAS:64742-47-8
RTECS #:OA5504000
Fraction by Wt: 0.55%

Ingred Name:ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL
CARBINOL
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 0.15%
Other REC Limits:400 PPM
OSHA PEL:400 PPM
ACGIH TLV:400 PPM

Ingred Name:V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS
CAS:8032-32
-4
RTECS #:OI6180000
Fraction by Wt: 7.03%
Other REC Limits:STEL 400 PPM
OSHA PEL:300 PPM
ACGIH TLV:300 PPM

Ingred Name:2-BUTOXYETHANOL (ETHYLENEGLYCOL MONOBUTYL ETHER), BUTYL
CELLOSOLVE, BUTYL GLYCOL, GLYCOL ETHER EB
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 1.07%
Other REC Limits:25 PPM (SKIN)
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 18%
Other REC Limits:1800 MG/CUM
OSHA PEL:1000 PPM
ACGIH TLV:SIMPLE ASPHYXIAN

ingred Name:ISOBUTANE, 2-METHYLPROPANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 12%
Other REC Limits:1000 PPM
OSHA PEL:1800 MG/CUM
ACGIH TLV:1000 PPM

ingred Name:WEIGHT PER GALLON IN POUNDS: 6.829
RTECS #:9999999WG

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:INHALATION: RESPIRATORY TRACT
IRRITATION, HEADACHE, DIZZIN
ESS, NAUSEA, UNCONSCIOUSNESS &
ASPHYXIATION. EYES: IRRITATION.
Explanation of Carcinogenicity:SEE INGREDIENTS
Effects of Overexposure:INHALATION: CNS DEPRESSION, DROWSINESS,
NARCOSIS, CARBOXYHEMOGLOBINEMIA. LIVER & KIDNEY EFFECTS. DAMAGES
DEVELOPING FETUS. SKIN: DEFATTING, IRRITATION & DERMATITIS.
INGESTION: GI IRRITATION, VOMITING, DIARRHEA, ASPIRATION INTO
LUNGS CAUSES CHEMICAL PNEUMONITIS.

=====
===== First Aid Measures =====

First Aid:INH
ALATION: REMOVE TO FRESH AIR. GIVED CPR IF NEEDED. EYES:
FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER. INGESTION:
OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:AEROSOL -10F
Extinguishing Media:CO2, DRY CHEMICAL OR FOAM.
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. USE WATER TO
COOL CONTAINERS TO PREVENT BURSTING. IF WATER IS USED, FOG NOZZLES
ARE PREFERABLE. USE

SCBA.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. WIPE UP W/INERT MATERIALS & PLACE IN APPROPRIATE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 120F. USE W/ADEQUATE VENTILATION. USE ONLY AS DIRECTED.

Other Precautions:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPORS & INHALING THE CONTENTS CAN BE HARMFUL OR FATAL. AVOID BREATHING OF VAPORS & SPRAY MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A SELF CONTAINED BREATHING APPARATUS REQUIRED FOR CONCENTRATIONS ABOVE TLV LIMITS.

Ventilation:VENTILATION SUFFICIENT TO PREVENT INHALATION OF VAPORS

Protective Gloves:OPTIONAL

Eye Protection:RECOMMENDED

Supplemental Safety and Health

=====

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>1

Evaporation Rate & Reference:FASTER THAN ETHER

Appearance and Odor:RED PAINT

Percent Volatiles by Volume:82/WT

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS.

Stability Condition to Avoid:TEMPS ABOVE 120F, SPARKS, OPEN FLAME OR OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:CO2 & CO

=====

Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE AEROSOL, DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATONS. DO NOT PLACE AEROSOL CANS IN HOME COMPACTOR. DO NOT PUNCTURE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.