

3M COMPANY-ADHESIVES,COATINGS & SEALERS DIV -- SCOTCHWELD 2216A ADHESIVE
(TRANSLUCENT) -- 8040-00-145-0019

=====
Product Identification
=====

Product ID:SCOTCHWELD 2216A ADHESIVE (TRANSLUCENT)

MSDS Date:01/01/1987

FSC:8040

NIIN:00-145-0019

Kit Part:Y

MSDS Number: BDCBR

=== Responsible Party ===

Company Name:3M COMPANY-ADHESIVES,COATINGS & SEALERS DIV

Emergency Phone Num:612-733-1110(OP55)

CAGE:04

963

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC AMINE

Fraction by Wt: 60.0%

=====
Hazards Identification
=====

Effects of Overexposure:EYE:EXTR IRRT MAY CAUSE PERM EYE

DAMAGE.SKN:IRRRT&SENS

.INHAL:IRRRT.INGES:IRRRT GI TRACT

=====
First Aid Measures
=====

First Aid:EYE:FLUSH COPIOUSLY WATER 10 MIN. SKN:THOROUGH WASH SOAP &
WATER. INH:REMOVE TO FRESH AIR. INGES: DRINK TWO GLASSES MILK OR
WATER.CALL PHYSICIAN,INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point:>200F CC

Extinguishing Media:CO2,FOAM,DRY CHEMICAL, WATER

Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP

Unusual Fire/Explosion Ha

zard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA, COLLECT SPILLED MATERIAL,
CLEANUP RESIDUE,PLACE IN APPROVED METAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH EYE & SKIN.AVOID
INHAL OR EYE CONTACT WITH DUST FROM GRINDING OPERATIONS. WASH
CONTAMINATED CLOTHING BEFORE REUSE.

Other Precautions:VENT CURING OVENS TO OUTDOORS.KEEP
CONTAINERS CLOSED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE
VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:SCBA IN FIRE. USE DUST MASK WHEN GRINDING
CURED RESIN.

Supplemental Safety and Health

PART A OF TWO PART KIT. BASIS: MENT DTD 1 NOV 85 (OSHA HAZCOMSTD), 3M
DOCUMENT 1031731. 3M GENERIC P/N IN 62-3608-XXXX-X KIT A

LSO KNOWN

AS 2216B/A OR 3M EC2216B/A (TRANSLUCENT) KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:0.97

Viscosity:7000 CP

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER PASTE

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO2, N, SMOKE PARTICLES ON EXPOSURE
EXCESS HEAT OR FLAME

=====

= Disposal Considerations =====

Waste Disposal Methods:OBSERVE ALL APPLICABLE REGS BEFORE DISPOSAL.
CURED RESIN (A&B):DISPOSE IN SAND LANDFILL. SPILL:DISPOSE OF
CLEANUP MATL BY INCNERATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disc

laims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.