

AKZO COATINGS INC -- BOSTIK -- 8010-00-181-8296

=====  
Product Identification  
=====

Product ID:BOSTIK  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-181-8296  
Kit Part:Y  
MSDS Number: BDGVJ  
=== Responsible Party ===  
Company Name:AKZO COATINGS INC  
Address:434 W. MEATS STREET  
City:ORANGE  
State:CA  
ZIP:92661  
Country:US  
Info Phone Num:714-637-1750  
Emergency Phone Num:714-637-1750; CHEMTREC 800-424-9300  
CAGE:98502

=== Contractor Identification ===  
Company Name:AKZO COATINGS INC  
Address:434 W. MEATS STREET  
Box:City:ORANGE  
State:CA  
ZIP:92661  
Country:US  
Phone:714-637-1750; CHEMTREC 800-424-9300  
CAGE:98502

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SOLVENTS  
Fraction by Wt: 45.0%  
ACGIH TLV:100-400 PPM

Ingred Name:POLYESTER RESIN  
Fraction by Wt: 19.1%

Ingred Name:ISOCYANATE PREPOLYMER (ALIPHATIC)  
Fraction by Wt: 19.2%

Ingred Name:PIGMENTS  
Fraction by Wt: 19.2%

Ingred

Name:ADDITIVES  
Fraction by Wt: 0.2%

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALE-IRRITATE NOSE & THROAT. MAY CAUSE NAUSEA OR VOMITING. MAY CAUSE EYE & SKIN IRRITATION.

=====  
First Aid Measures  
=====

First Aid:SKIN-WASH WITH SOAP & WATER. EYE-FLUSH WITH WATER; CONSULT DOCTOR. INHALE-REMOVE TO FRESH AIR;CONSULT DOCTOR. INGESTION. INDUCE VOMITING; CONSULT DOCTOR.

=====  
Fire Fighting Measures  
=====

Flash Point:23F, -5C TCC  
Lower Limits:1.1  
Extinguishing Media:CO2 OR DRY CHEM FOR SMALL;ALCOHOL FOAM FOR LARGE FIRES.  
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. USE AIR SUPPLIED RESCUE EQUIPMENT.  
Unusual Fire/Explosion Hazard:DO NOT APPLY TO HEATED SURFACES OR IN AREAS WHERE ELECTRICAL SPARKS MAY BE PRESENT.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ABOSRB WITH SAWEDUST OR OIL ABSORBING COMPOUND. WASH AREA WITH DETERGENT AND WATER. USE ADEQUATE VENTILATION TO CLEAR FUMES FROM AREA. AVOID SPARKS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE UNDER 100F. KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE.  
Other Precautions:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:AIR SUPPLIED R

ESPIRATOR OR SUITABLE CHEMICAL  
CARTRIDGE.

Ventilation:TO MEET TLV

Protective Gloves:SOLVEN RESISTAN

Eye Protection:GOGGLES OR FACE SHIELD

Other Protective Equipment:COVERALLS, APRON, NON-SPARKING SAFETY SHOES,  
ETC.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-320F

Vapor Density:>AIR

Evaporation Rate & Reference: