

SUN REFINING AND MARKETING COMPANY -- SR 4210 SAE 10;MOTOR OIL -- 9150-00-189-6727

===== Product Identification =====

Product ID:SR 4210 SAE 10;MOTOR OIL

MSDS Date:02/16/1990

FSC:9150

NIIN:00-189-6727

MSDS Number: BDHRS

=== Responsible Party ===

Company Name:SUN REFINING AND MARKETING COMPANY

Address:1801 MARKET ST.TEN PENN CENTER; 18 FLOOR

City:PHILADELPHIA

State:PA

ZIP:19103-1699

Country:US

Info

Phone Num:215-977-6133 OR 215-293-9270

Emergency Phone Num:215-977-6133

CAGE:8X531

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

Company Name:SUN REFINING AND MARKETING COMPANY

Address:1801 MARKET ST,TEN PENN CTR

Box:City:PHILADELPHIA

State:PA

ZIP:19103-1699

Country:US

Phone:215-977-6133

CAGE:8X531

===== Composition/Information on Ingredients =====

Ingr

ed Name:REFINED HEAVY PARAFFINIC DISTILLATES  
CAS:64741-88-4  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ZINC DIALKYL DITHIOPHOSPHATE  
CAS:68457-79-4  
Fraction by Wt: 1.35%

Ingred Name:BORATED ISOBUTENYL SUCCINIC ANHYDRIDE

Ingred Name:MAGNESIUM ALKARYL DETERGENT

Ingred Name:METHACRYLATE COPOLYMER

Ingred Name:ZINC (SARA III)  
CAS:7440-66-6  
RTECS #:ZG8600000  
Fraction by Wt: 0.12%  
OSHA PEL:10 MG ZNO/M3  
ACGIH TLV:10 MG ZNO/M3; 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:PHOSPHOROUS (YELLOW) (SARA III)  
CAS:7723-14-0  
RTECS #:TH3500000  
Fraction by Wt: 0.11%  
OSHA PEL:0.1 MG/M3  
ACGIH TLV:0.1 MG/M3; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) =>5 GM/KG  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF  
EYES,SKIN,RESPIRATORY OR G.I.TRACTS;CN

## S EFFECTS LIKE

HEADACHE,DIZZINESS,NAUSEA AND VOMITING.CHRONIC:DRYING OF SKIN,DEFATTING OR DERMATITIS POSSIBLE.

Effects of Overexposure:INHALED:>25 MG/CUM MAY PRESENT PROBLEMS.SKIN:IRRITATS W PROLONGED EXPOS.EYES:SLIGHT IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

## ===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

## ===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:380F,193C

Autoignition Temp:Autoignition Temp Text:695F

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:CAN BE MADE TO BURN; FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

## ===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE MATERIAL IF POSSIBLE;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL IN AN APPROVED CONTAINER.

Neutralizing Agent:NOT APPLICABLE.

## ===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.A

VOID ANY PHYSICAL CONTACT.

KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:PROLONGED OR REPEATED CONTACT WITH USED OIL MAY HARM SKIN & COULD CAUSE CANCER.PROMPTLY WASH AFFECTED AREA WITH SOAP AND WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR AS REQUIRED IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.WASH THOROUGHLY AFTER EACH USE.

=====

= Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:WIDE RANGE

Vapor Pres:NIL

Vapor Density:>10

Spec Gravity:0.87

pH:6.6

Evaporation Rate & Reference:0.001(ETHER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK FLUID,ENGINE OIL ODOR;PH 6.6.

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES,

SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND  
OTHER UNIDENTIFIED COMPONENTS.

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES.DISPOSAL MUST BE MADE  
IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Departmen

t  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.