View NSN Online: https://aerobasegroup.tw/nsn/6510-00-200-0160

BEETON DICKINSON & CO -- ADHESIVE LIQUID, SURGICAL/ETHYL ACOHOL -- 6510-00-200-0160

Product ID:ADHESIVE LIQUID,SURGICAL/ETHYL ACOHOL MSDS Date:01/01/1985 FSC:6510 NIIN:00-200-0160 **MSDS Number: BDJFM** === Responsible Party === Company Name: BEETON DICKINSON & CO Address:1 BECTON DR **City:FRANKLIN LAKES** State:NJ ZIP:07417-1880 Country:US Emergency Phone Num:NONE CAGE:K O577 === Contractor Identification === Company Name: BECTON DICKINSON AND CO, BECTON DICKINSON DIV. Address:1 BECTON DR **City:FRANKLIN LAKES** State:NJ ZIP:07417-1884 Country:US Phone:201-847-4000, 800-333-4831 CAGE:06531 Company Name: BEETON DICKINSON & CO Address:1 BECTON DR Box:City:FRANKLIN LAKES State:NJ ZIP:07417-1880 Country:US CAGE:KO577

Ingred Name:ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 OSHA PEL:1000 PPM AC

GIH TLV:1000 PPM; 9192

	Hazards Identification	
--	------------------------	--

Effects of Overexposure: IRRIGATION OF EYES & RESPIRATORY TRACT; HEADACHE, DIZZINESS, DROWSINESS, MENTAL CONFUSION, FATIGUE, NAUSEA

First Aid:IRRIGATE EYES W/WATER,STOMACH ASH,IF SWALLOWED,FOLLOWED BY SALINE CATHARSIS

Flash Point Method:TCC Flash Point:=12.2C, 53 .9F Lower Limits:3.3 Upper Limits:19.0 Extinguishing Media:DRY CHEMICAL,FOAM,OR CARBON DIOXIDE,WATER SPRAY INEFFECTIVE. Unusual Fire/Explosion Hazard:FLAME,FIRE,IGNITION SOURCES MAY PRODUCE EXPLOSION

Spill Release Procedures:NO FLARES,SMOKING OR FLAMES IN HAZARD AREA.STOP LEAK IF WITHOUT RISK.USE WATER SPRAY TO REDUCE VAPORS.LARGE SPILLS DIKE FOR LATER DISPOSAL.SMALL SPILLS:TAKE UP WITH SAND,EARTH,OR OTHER NONCOMBUSTIBLE ABSORBENT MATERIAL.

Handling and Storage Precautions:PROTECT CONTAINERS AGAINST PHYSICAL DAMAGE.STORE AWAY FROM POSSIBLE IGNITION SOURCES.ALL PRECAUTIONS FOR THE ELIM.OF STATIC ELECTRICITY BE TAKEN.
Other Precautions:AVOID STORAGE WITH PERCHLORATES,PEROXIDES,CHROMIC ACID & NITRIC ACID.WEAR CHEMICAL GOGGLES,CHEMICAL CARTRIDGE RESPIRATOR,RUBBER GLOVES & RUBBER BOOTS.

======= Exposure Contr

ols/Personal Protection =========

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS OR CHEMICAL CARTRIDGE RESPIRATOR Ventilation:AS REQUIRED TO CONTROL TLV IN AIR Protective Gloves:RUBBER Eye Protection:CHEMICAL GOGGLES Other Protective Equipment:RUBBER BOOTS. Supplemental Safety and Health

HCC:F2 Boiling Pt:=78.5C, 173.3F Spec Gravity:0.80 Solubility in Water:APPRECIABLE Appearance and Odor:COLORLESS,HYGROS COPIC,VOLATILE LIQUID,PLEASANT. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES OXIDIZING MATLS,PERCHLORATES,PEOXIDES,CHROMIC ACID,HNO*3

Waste Disposal Methods:SPRAY INTO A FURNACE UNDER APPROVED CONTROLLED CONDITIONS.INCINERATION WILL BECOME EASIER BY MIXING WITH A MORE FLAMMABLE SOLVENT.

Disclaimer (provided with this i

nformation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.