View NSN Online: https://aerobasegroup.tw/nsn/3439-00-220-3825

J.W.HARRIS CO.,INC. -- STAY SILV BRAZING FLUX(BLACK OR WHITE) -- 3439-00-220-3825

Product ID:STAY SILV BRAZING FLUX(BLACK OR WHITE)

MSDS Date:11/01/1985

FSC:3439

NIIN:00-220-3825

MSDS Number: BDJTH === Responsible Party ===

Company Name: J.W.HARRIS CO., INC. Address: 10930 DEERFIELD ROAD

City:CINCINNATI

State:OH

ZIP:45242-4110

Country:US

Emergency Phone Num:513-891-

2000

CAGE:27911

=== Contractor Identification ===

Company Name: J. W. HARRIS CO., INC.

Address:10930 DEERFIELD ROAD

Box:City:CINCINNATI

State:OH

ZIP:45242-4110

Country:US

Phone:513-891-2000

CAGE:27911

======= Composition/Information on Ingredients ========

Ingred Name: BORON OXIDE

CAS:1303-86-2

RTECS #:ED7900000 Fraction by Wt: >5%

OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

Ingred Name: SODIUM TETRABORATE, DECAHYDRATE

CAS:1303-96-4

RTECS #:VZ2275000 Fraction by Wt: >25%

OSHA P

Ingred Name:FLUORIDES,FLUORATES AS F,CAS#NOT LISTED Fraction by Wt: >25% OSHA PEL:2.5 MG/CUM (HF) ACGIH TLV:2.5 MG/CUM (HF)
Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000
======================================
Effects of Overexposure:FUMES ARE IRRITATING TO SKIN,EYES AND RESPIRATORY TRACT.
======================================
First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF
BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP&WATER. RMV CONTAM CLTHG&SHOES. INGEST:INDUCE VOMIT. RPT UNTIL VOMIT IS C LEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.
======================================
Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:OPEN FLAME & SPARKS CAN IGNITE COMBUSTIBLES.
========= Accidental Rel ease Measures ==============
Spill Release Procedures:LG SPILLS SHOULD BE NEUTRALIZED W.A SLAKED LIME-SODA ASH SLURRY.PLACE IN SUITABLE DOT APPVD DISPOSAL CONTAINERS.
======================================
Other Precautions:TRAIN EMPLOYEE TO KEEP HIS HEAD OUT OF THE FUMES***FILLER METALS MAY CONTAIN CD.FUMES GENERATD DURING BRAZING WITH CD ALLOYS MAY BE TOXIC.
====== Exposure Controls/Personal Protection ========
Respiratory Pr

EL:10 MG/M3

ACGIH TLV:5 MG/M3; 9192

otection:FUME RESP.OR AIR SUPPLIED RESP.IN CONFINED SPACES.
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:WELDER'S GLOVES Eye Protection:FACE SHIELD W.FILTER LENS Other Protective Equipment:SUBST.DK.CLOTH,ARM
PROTECTOR,APRON,HAT,SHOULDR PROTECTION. Supplemental Safety and Health
========= Physical/Chemical Properties ============
HCC:N1 Appearance and Odor:WHITE PASTE-NO ODOR
========= Stability and Reactivity Data ===========
Stabi ity Indicator/Materials to Avoid:YES NONE SPECIFIED
Stability Condition to Avoid:NONE SPECIFIED Hazardous Decomposition Products:FLUORIDE FUMES.
======== Disposal Considerations ==============
Waste Disposal Methods:DISPOSE OF IAW LOCAL,STATE AND FEDERAL REGS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expr

essly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.