

MARSHALLTOWN INSTRUMENTS -- N TYPE OF STENCIL INK -- 7510-00-224-6732

=====  
Product Identification  
=====

Product ID:N TYPE OF STENCIL INK

MSDS Date:01/01/1987

FSC:7510

NIIN:00-224-6732

MSDS Number: BDKLM

=== Responsible Party ===

Company Name:MARSHALLTOWN INSTRUMENTS

Address:108 S COLORADO AVE

Box:1469

City:HASTINGS

State:NE

ZIP:68902

Country:US

Info Phone Num:402-463-6851

Emergency Phone Num:402

-463-6851

CAGE:72101

=== Contractor Identification ===

Company Name:MARSH STENCIL MACHINE CO

Address:707-EAST B STREET

Box:388

City:BELLEVILLE

State:IL

ZIP:62222

Country:US

Phone:618-234-1122

CAGE:38512

Company Name:MARSHALLTOWN INSTRUMENTS

Address:108 S COLORADO AVE

Box:1469

City:HASTINGS

State:NE

ZIP:68902

Country:US

Phone:402-463-6851

CAGE:72101

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PIGMENTS

Ingred Name:VEHICLE

Ingred Name:NAPHTHA (PETROLEUM SPIR

ITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:SE7555000  
OSHA PEL:100 PPM

Ingred Name:PETROLEUM HYDROCARBONS

===== Hazards Identification =====

Effects of Overexposure:CONTAINS MINERAL SPIRITS AND KEROSENE SLIGHT TO MODERATE SKIN IRRITANTS.

===== First Aid Measures =====

First Aid:CONTAINS PETROLEUM MAPHTHA.IF SWALLOWED.DO NOT INDUCE VOMITING.CALL PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:105-120 F CC 41  
Extinguishing Media:CARBON DIOXIDE (SAX DANGEROUS PROPERTIES)  
Fire Fighting Procedures:SAME AS PAINT  
Unusual Fire/Explosion Hazard:COMBUSTIBLE.DO NOT USE NEAR FIRE OR FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB IN SAWDUST OR CLOTH. CLEAN W/NAPHTHA. WASH WITH SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:DRY INSIDE STORAGE MAXIMUM TEMPERATURE 120F AVOID PROLONGED CONTACT W/SKIN OR BREATHING OF VAPOR.  
Other Precautions:FOR ACCIDENTAL EYE CONTACT-FLUSH W/WATER AND CONTACT PHYSICIAN IMMEDIATELY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE,EXCEPT IF INK IS SPRAYED  
Ventilation:LOCAL EXHAUST-DESIRABLE IF WORK AREA IS SMALL AND CONFINING  
Eye Protection:SEE PRECAUTIONS BELOW  
Supplemental Safety and Health  
300-500 F 149 C-260 C

=====

== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300-500 F

Vapor Pres:C20

Vapor Density:4-5

Spec Gravity:.86/1

Evaporation Rate & Reference:SLOW

Solubility in Water:NONE

Appearance and Odor:VARIOUS COLORS-NAPHTHA ODOR

Percent Volatiles by Volume:65-7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

LACQUER THINNER AND ALCOHOL

Hazardous Decomposition Products:WHEN EXPOSED TO FLAME,SOLVENT CAN

REACT W/OXIDIZING MATERIAL

Conditions to Avoid Polymerization:STORAGE ABOVE 120 F

===== Disposal Considerations =====

Waste Disposal Methods:SAME AS PAINT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for it

s use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.