

SOUTHWEST PETRO-CHEM -- SF 871 1010 -- 9150-00-231-2361

=====
Product Identification
=====

Product ID:SF 871 1010

MSDS Date:01/01/1987

FSC:9150

NIIN:00-231-2361

MSDS Number: BDKYS

=== Responsible Party ===

Company Name:SOUTHWEST PETRO-CHEM

Emergency Phone Num:913-782-5800

CAGE:70878

=== Contractor Identification ===

Company Name:EXXON CO USA-SOUTHWEST GREASE BUSINESS UNIT

Address:1400 S HARRISON

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:913-656-3701/800-424-9300(CHEMTREC)

CAGE:70878

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL; CAS #64742-52-5

CAS:64742-52-5

RTECS #:PY8035000

ACGIH TLV:5MG/CUM(MIST)

Ingred Name:BARIUM SULFONATE; CAS #61790-48-5

Ingred Name:THICKENING AGENT

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE SKIN & EYE IRRITATION WITH PROLONGED
CONT

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.926

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER,OIL-LIKE LIQUID,WITH MINERAL OIL ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS:H*2O*2,CROMIC

Stability Condition to Avoid:HEAT, IGNITION SOURCES

Hazardous Decomposition Products:CO,CO*2,ACID,BROMINE.

=====

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to
be accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.