

BATTENFELD -- VV-L-800 -- 9150-00-231-6689

=====
Product Identification
=====

Product ID:VV-L-800

MSDS Date:01/01/1987

FSC:9150

NIIN:00-231-6689

MSDS Number: BDLCG

=== Responsible Party ===

Company Name:BATTENFELD

Emergency Phone Num:(716)822-8410

CAGE:60229

=== Contractor Identification ===

Company Name:BATTENFELD

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120

Country:US

Phone:716-695-2100

CAGE

:60229

Company Name:BATTENFELD GREASE AND OIL CORP OF NEW YORK INC

Address:1174 ERIE AVE

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120-3036

Country:US

Phone:716-695-2100

CAGE:60226

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, CAS #64742-53-6

CAS:64742-53-6

RTECS #:PY8036000

Fraction by Wt: 97%

ACGIH TLV:5MG/CUM(MIST)

Ingred Name:BARIUM SULFONATE

CAS:25619-56-1

RTECS #:CR0700000

Fraction by Wt: 2%

OSHA PEL:0.5 MG/M3 (BA)

ACGIH TLV:0.5 MG/M3 (B

A); 8990

Ingred Name:ZINC DIAMYL DITHIOCARBAMATE,CAS #15337-18-5

Fraction by Wt: 1.0%

=====
Hazards Identification
=====

Effects of Overexposure:EYE/SKIN:MILD IRRITANT

=====
First Aid Measures
=====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG
DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH
W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE
VOMIT. NOTHG BY MO
UTH IF UNCONSC. GET MEDICAL ATTN.

=====
Fire Fighting Measures
=====

Flash Point:380F,193C,COC
Autoignition Temp:Autoignition Temp Text:430F
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WTR MAY CAUSE FROTHING
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AREA
WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS,
SUCH AS
SAWDUST,RAGS,PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING
TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED LOW FIRE
RISK AREA. PROTECT FROM HEAT,SHOCK,FRICITION. KEEP CONTAINERS
CLOSED.
Other Precautions:WASH THOROUGHLY AFTER HANDLING.DO NOT GET IN HANDS OR
ON CLOTHING.

=====
Exposure Controls/Personal Protection

=====
Ventilation:NO SPECIAL REQUIREMENTS W ADEQUATE VENT.
Protective Gloves:NEOPRENE,POLYET
Other Protective Equipment:NONE
Supplemental Safety and Health
UNDATED MSDS/

=====
Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:600F,316C
Vapor Pres:0
Spec Gravity:0.90
Solubility in Water:NEGL
Appearance and Odor:AMBER OIL-BLAND ODOR
Percent Volatiles by Volume:0

=====
Stability and Reactivity Data =====

Stability Ind
icator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:NONE SPECIFIED
Hazardous Decomposition Products:OXIDES OF CARBON AND SULFUR

=====
Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by el
ements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.