

VAN WATERS AND ROGERS INC -- XYLENE -- 6810-00-257-2479

===== Product Identification =====

Product ID:XYLENE
MSDS Date:01/16/1989
FSC:6810
NIIN:00-257-2479
MSDS Number: BDPHL
=== Responsible Party ===
Company Name:VAN WATERS AND ROGERS INC
Address:2600 CAMPUS DRIVE
Box:5932
City:SAN MATEO
State:CA
ZIP:94403-2522
Country:US
Info Phone Num:415-573-8000
Emergency Phone Num:714-864-2310
CAGE:0AN91

===

Contractor Identification ===
Company Name:CHEMICAL COMMODITIES AGENCY, INC.
Address:27447 PACIFIC STREET
Box:City:HIGHLAND
State:CA
ZIP:92346-2640
Country:US
Phone:909-864-2310
CAGE:60777
Company Name:VAN WATERS AND ROGERS
Address:2256 JUNCTION AVE
City:SAN JOSE
State:CA
ZIP:95131
Country:US
Phone:408-435-8700/800-424-9300(CHEMTREC)
CAGE:0AN91

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000

Fraction by Wt: 80%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 20%
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:LD 50 RAT(ORAL) IS 4.3 G/KG.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION OF VAPORS AND MISTS IRRITATE MUCOUS MEMBRANES. INHALATION OF HIGHER CONCENTRATIONS MAY CAUSE HEADACHES, NAUSEA, VOMITING, AND COMA. INHALATION OF VERY HIGH CONCENTRATIONS MAY CAUSE UNCONSCIOUSNESS OR DEATH. CHRONIC: PROLONGED OR REPEATED EXPOSURE TO HIGH CONCENTRATIONS MAY CAUSE NEURAL DYSFUNCTION.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC,
NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:LIQUID AND MIST MAY IRRITATE THE EYES. BRIEF CONTACT MAY DRY THE SKIN. PROLONGED OR REPEATED CONTACT MAY IRRITATE THE SKIN, CAUSING DERMATITIS. SEE HEALTH HAZARDS FOR INHALATION. SWALLOWING THE LIQUID MAY RESULT IN VOMITING. DO NOT ALLOW VOMITUS TO BE BREATHED INTO THE LUNGS. SM. QUAN. COULD LEAD TO PNEUMONITIS, ETC.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT

INDUCE
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:79.0F,26.1C
Lower Limits:1
Upper Limits:7
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG. DO NOT USE A DIRECT WATER STREAM.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER

SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:AVOID ACCUMULATION OF WATER BECAUSE THIS
PRODUCT WILL FLOAT ON WATER AND MAY REIGNITE ON THE SURFACE OF THE
WATER.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP PEOPLE AWAY.
RECOVER FREE LIQUID. ADD ABBSORBENT(SAND, EARTH, SAWDUST, ETC.) TO
SPILL AREA. AVOID BREATHING VAPORS. VENTILATE CONFINED SPACES. OPEN
ALL WIN
DOWS AND DO ORS.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG
OXIDANTS. VENTILATION EQUAL TO OUTDOORS REQUIRED.
Other Precautions:AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. REMOVE
CONTAMINATED CLOTHING, LAUNDER BEFORE REUSE. WASH SKIN THOROUGHLY
WITH SOAP AND WATER AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE HYDROCARBON VAPOR CANISTER OR SUPPLIED-AIR
RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES IF NEEDED.
Ventilation:LOCAL MECHANICAL EXHAUST VENTILATION CAPABLE OF MAINTAINING
EMISSIONS AT THE POINT OF USE BELOW THE PEL.
Protective Gloves:CHEMICAL RESISTANT
Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.
INDUSTRIAL-TYPE WO

RK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:281F,138C

Melt/Freeze Pt:M.P/F.P Text: