

AMERICAN & OIL SUPPLY CO -- VV-L-800C (LUBRICATING OIL) -- 9150-00-273-2389

=====
Product Identification
=====

Product ID:VV-L-800C (LUBRICATING OIL)

MSDS Date:01/01/1987

FSC:9150

NIIN:00-273-2389

MSDS Number: BDRZZ

=== Responsible Party ===

Company Name:AMERICAN & OIL SUPPLY CO

Emergency Phone Num:(201)589-0250

CAGE:LO080

=== Contractor Identification ===

Company Name:AMERICAN & OIL SUPPLY CO

CA

GE:LO080

Company Name:AMERICAN OIL AND SUPPLY CO

Address:239 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Phone:201-589-0250

CAGE:92895

=====
Composition/Information on Ingredients
=====

Ingred Name:LUBRICATING OIL

Fraction by Wt: 100%

ACGIH TLV:5MG/CUM(MIST)

=====
Hazards Identification
=====

Effects of Overexposure:EYE:IRR,RED;SKIN:IRR,DEFAT;INH:NASAL

IRR,DIZZ,WEAK,NAUSEA,HEAD,UNCONSC;ING:NAUSEA,VOMIT,DIARR,GI IRR

=====

=====
First Aid Measures
=====

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.

INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

ING:SEEK MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point:275F,135C,COC

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL
CONTR.

Unusual Fire/Explosion Hazard:DO NOT USE D

IRECT STREAM OF WTR MATERIAL
MAY FLOAT AND REIGNITE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AREA WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS SAWDUST,RAGS,PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.KEEP PROD OUT OF WTRWAYS

===== Handling and Storage =====

Handling and Storage

Precautions:STORE IN COOL,DRY WELL VENTED LOW FIRE RISK AREA. PROTECT FROM HEAT,SHOCK,FRICITION. KEEP CONTAINERS CLOSED.

Other Precautions:AVOID BREATHING OF MISTS OR SPRAYS.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN & PROD.VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQD.NIOSH APPVD RESP IF TLV IS EXCEEDED

Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.

Protective Gloves:NEOPRENE

Eye Protection:G

OGGLES/FACE SHIELD

Other Protective Equipment:WEAR IMPERVIOUS CLOTHING & BOOTS.

Supplemental Safety and Health

MSDS DATED NOV.85/

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:430F,221C

Vapor Pres:6

Spec Gravity:0.89

Evaporation Rate & Reference: