

AMERON INDUSTRIAL COATINGS DIVISION -- 728-010;PRIMER,FORMULA 117B;MIL-P-15328C --
8030-00-281-2726

===== Product Identification =====

Product ID:728-010;PRIMER,FORMULA 117B;MIL-P-15328C

MSDS Date:01/01/1985

FSC:8030

NIIN:00-281-2726

MSDS Number: BDSTL

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Inf

o Phone Num:714-529-4597

Emergency Phone Num:714-529-4597

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 52.7%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:N-BUTYL ALC

OHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 19.3%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC CHROMATE
CAS:13530-65-9
RTECS #:GB3290000
Fraction by Wt: 8.4%
OSHA PEL:0.1 MG/M3 (CRO3)
ACGIH TLV:0.01MG/M3(CR)A1;9192

=====
===== Hazards Identification =====

Effects of Overexposure:INH:ANESTHETIC, IRRIT OF RESP TRACT OR ACUTE
CNS DEPRSSN W/HDACHE,DIZ,UNCON,COMA. SKIN & EYE:IRRIT

=====
===== First Aid Measures =====

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE
REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR.
CALL A MD IF SYMPTOMS PERSIST.

=====
===== Fire Fighting Measures =====

Flash Point:59F TCC
Lower Limits:2.5
Extinguishing Media:SM FIRES:CO*2, DRY CHEM. LG FIRES:POLYMER FOAM
PREFERRED
Fire Fighting Procedures:USE SELF-CONTANED BREATHING APPARATUS
Unusual F
ire/Explosion Hazard:CLOSED CONTANERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME, HOT
SURFACES& ELECTRICAL,STATIC OR FRICTIONAL SPARKS).AVOID BREATHING
VAPORS. VENTILATE AREA.REMOVE W/INERT ABSRBENT & NON-SPARKING
TOOLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABO

VE 120F.STORE LG QTY

IN BLDG DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ DO NOT TAKE INTERNALLY. ADD LABEL WARNING.

Other Precautions:GROUND CONTANERS WHEN POURING. AVOID FREE FALL OF LIQ IN EXCESS OF FEW IN. DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL W/O APPROVED RESPIRATOR OR APROPRIATE VENTILATION. DOT:FLAM LIQ

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR.CLSD:AIR-LINE TYPE

Ventilation:GEN DILT/LOC

AL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV

FUME

Protective Gloves:YES

Eye Protection:YES FOR SPLASH

Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING

Supplemental Safety and Health

VAPOR PRESSURE;31.2;VAPOR DENSITY;HEAVIER THAN AIR;WT PER GALLON:7.8

LBS. AOT-LD50 IS 1.8G/KG FOR ZINC CHROMATE.

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-208F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Vo

lume:87.7

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES

=====
===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER. DISPOSE IN ACCORDANCE W/FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the

Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.