

VENTRON CORP DIV OF/THIOKOL -- MIL-C-11135,CAL HYD CHARGE,ML-304(A)/TM
6660-00-408-4559

=====
Product Identification
=====

Product ID:MIL-C-11135,CAL HYD CHARGE,ML-304(A)/TM

MSDS Date:01/01/1985

FSC:6660

NIIN:00-408-4559

MSDS Number: BDXXD

=== Responsible Party ===

Company Name:VENTRON CORP DIV OF/THIOKOL

Address:150 ANDOVER ST

City:DANVERS

State:MA

ZIP:01923-1428

Country:US

CAGE:LO329

=== Cont

actor Identification ===

Company Name:THIOKOL CORP VENTRON DIVISION

Address:150 ANDOVER ST

Box:City:DANVERS

State:MA

ZIP:01923-1428

Country:US

CAGE:01785

Company Name:VENTRON CORP DIV OF/THIOKOL

Address:150 ANDOVER ST

Box:City:DANVERS

State:MA

ZIP:01923-1428

Country:US

CAGE:LO329

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM HYDROXIDE

CAS:1305-62-0

RTECS #:EW2800000

Fraction by Wt: 94.0%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:5 MG/M3; 9293

=====

=====
Hazards Identification
=====

Effects of Overexposure:SKIN CONTACT CAN CAUSE ALKALI BURNS.

=====
First Aid Measures
=====

First Aid:AVOID SKIN,EYES OR CLOTHING CONTACT.SKIN CONTACT SHOULD BE BRUSH OFF FOLLOWED BY THOROUGH FLUSHING W WATER UNDER PRESSURE:CAUSTIC BURN MAY RESULT.TREAT ACCORDINGLY.GET MED ATTN.

=====
Fire Fighting Measures
=====

Extinguishing Media:DRY CHEMICAL

Fire Fightin

g Procedures:COVER SPILLAGE W DRY POWDER LIMESTONE &DISPOSE OF SAFELY.

Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION;EVOLVES HYDROGEN GAS ABOVE 600C(1112F)

=====
Accidental Release Measures
=====

Spill Release Procedures:SWEEP-UP(WITH DRY IMPLEMENTS);DECOMPOSE IN LARGE EXCESS OF WATER IN WELL VENTILATED AREA.ALL IGNITION,SPARK GENERATING SOURCES & HEATER MUST BE ELIMINATED BEFORE DECOMPOSING IN WATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:MINIMIZE EXPOSURE TO AIR OF HIGH HUMIDITY;AVOID CONTACT W WATER.CALCIUM HYDRIDE REACTS W WATER TO GIVE HYDROGEN GAS & CALCIUM HYDROXIDE

Other Precautions:PROTECT CONTNR AGAINST PHYSICAL DAMAGE.EMPTY CONTNR MAY BE HAZARDOUS.OBSERVE ALL HAZ PRE CAUTIONS FOR EMPTY CONTNRS OF THIS MATL.STORE IN DRY AREA,AWAY FROM SOURCE OF WATER/MOISTURE.

=====
Exposure Controls/Personal Protection
=====

Ventilation:A

S REQD TO CONTROL DUST IN AIR.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:IMPERVIOUS CLOTHING TO AVOID SKIN CONTACT.

Supplemental Safety and Health

PER MFR 6/2/82,THE ACTIVE INGREDIENT OF ONE CAL HYD CHARGE IN A HERMATICALLY SEALED CAN IS APPROX 0.4 POUND.

=====
Physical/Chemical Properties
=====

HCC:F8

Spec Gravity:1.9

Solubility in Water:REACTIVE

Appearance and Odor:ODORLESS,GRAY SOLID

Percent Volatiles by Volume:

NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

WATER, ORGANIC ACIDS, LOWER ALCOHOLS.

Stability Condition to Avoid: MOISTURE & WATER CONTACT; HEATING ABOVE
600C/1112F.

Hazardous Decomposition Products: HYDROGEN GAS

===== Disposal Considerations =====

Waste Disposal Methods: DECOMPOSE IN LARGE EXCESS OF WATER IN WELL
VENTILATED AREA, THEN DISPOSE OF SOLUTION OF $Ca(OH)_2$ IAW
LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their

particular situation.