

DEFT CHEMICAL COATINGS -- 03-R-26 CATALYST,RED 11136,ISOCYANATE -- 8010-00-482-5649

=====
Product Identification
=====

Product ID:03-R-26 CATALYST,RED 11136,ISOCYANATE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-482-5649

Kit Part:Y

MSDS Number: BDZYJ

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Emergency Phone N

um:NONE

CAGE:EO418

=== Contractor Identification ===

Company Name:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====
Composition/Information on Ingredients
=====

Ingred Name:BIURET OF 1,6 HEXAMETHYLENE DIISOCYANATE-SEE P/N IND "B"

FOR OTHER INGREDIENTS (NIOSH 1-5

Fraction by Wt: 30.0%

=====
Hazards Identification
=====

Effe

cts of Overexposure:SKIN/EYES:IRRITATION;INH:IRRIT OF RESP
TRACT/ACUTE NERVOUS SYSTEM DEPRESSION;HEADACHE,DIZZINESS,ETC.

=====
First Aid Measures
=====

First Aid:EYES:FLUSH IMMED W/LG VOLUME OF WTER FOR AT LEAST 15 MIN.GET
MED ATTN;SKIN:WASH AFFECTED AREA W/WATER.REMOVE CONTAMINATED
CLOTHING.GET MED ATTN IF IRRIT OCCURES;INH:REMOVE FROM
EXPOSURE.RESTORE BREATH ING BY CPR,KEEP WARM & QUIET.GET MED ATTN.

=====
Fire Fighting
Measures
=====

Flash Point:20F(-6.6C)-TCC
Extinguishing Media:CARBON DIOXIDE,FOAM OR DRY CHEM.(CLASS B FIRE
EXTINGUISHER)
Fire Fighting Procedures:SELF-CNTND BRTHG APP;WATER SPRAY TO COOL FIRE
EXPOSED CONTNR
Unusual Fire/Explosion Hazard:CLOSED CONTNRS MAY ECPLUDE IN HEAT OF
FIRE;SPILL/RUNOFF MAY CAUSE POLLUTION,FIRE,&/OR EXPLSION HAZRD

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIM IGN SOURCES.VENTILATE AREA.USE
PROTECTV
EQUIP.STOP LEAK W/O RISK.SM SPILL:CONTAIN/REMOVE W/INERT ABSORBENT
& NON-SPARKING TOOLS.PLACE IN COVERD CONTNRS;LG SPILL:DIKE AREA &
PUMP LIQ TO SALVAGE TA NK.ABSORB REMAINING LIQ & SHOVEL UP
INTOCONTAINR.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW
FIRE RISK AREA.DEEP CLOSURE TIGHT & CONTNR UPRIGHT.STORE AWAY FM
PHYSICALDAMAGE
Other Precautions:PREVENT PROLONGD/REPEA
TD BREATHING OF VAP OR SPRAY
MIST.CAN CAUSE ALLERGIC REACTION.FOLLOW SPECIAL PRECAUTIONS TO
APPLY ON HOT SURFACES.IF WATER IS USED FOR FIRE,FOG NOZZLES ARE
PREFERABLE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH APPROVED RESPIRATOR FOR
PAINT,LAQUER,ENAMEL MISTS/ORGANIC VAP.
Ventilation:ADEQUATE USING EXHAUS FAN OR IAW 29CFR PART 1910.94
Protective Gloves:NEOPRENE/RUBBER
Eye Protection:SAFETY GLASS W/SIDE SHLD.
Other Protectiv

e Equipment:CLEAN, LONG SLEEVE/LONG LEG PROTECTIVE
CLOTHING.

Supplemental Safety and Health

MSDS FM MFR DATED:10/28/80;TWO PART RESIN MODIFIED POLYURETHANE
COATING;SEE P/N IND "B" FOR OTHER INGREDIENTS OF THIS ITEM:SPEC REF
MIL-C-83286B,TYPE1.KEY1:F3.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-313F

Vapor Density:>1.0

Spec Gravity:0.9023

Evaporation Rate & Reference: