

MEASUREMENTS GROUP -- TYPE 361A-20R SOLDER -- 3439-00-522-2625  
===== Product Identification =====

Product ID:TYPE 361A-20R SOLDER  
MSDS Date:01/01/1985  
FSC:3439  
NIIN:00-522-2625  
MSDS Number: BFCLB  
=== Responsible Party ===  
Company Name:MEASUREMENTS GROUP  
Emergency Phone Num:919-365-3800  
CAGE:88952  
=== Contractor Identification ===  
Company Name:MEASUREMENTS GROUP INC  
Address:9517 US 64 HWY  
Box:City:  
WENDELL  
State:NC  
ZIP:27591  
Country:US  
Phone:919-365-3800  
CAGE:88952

===== Composition/Information on Ingredients =====

Ingred Name:TIN  
CAS:7440-31-5  
RTECS #:XP7320000  
Fraction by Wt: 63%  
OSHA PEL:2 MG/M3  
ACGIH TLV:2 MG/M3; 9192

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Fraction by Wt: 36.6%  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 MG/M3;DUST 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY (SARA III)  
CAS:7440-36-0  
RTECS #:CC4025000  
Fractio

n by Wt: 0.35%  
OSHA PEL:0.5 MG/M3  
ACGIH TLV:0.5 MG SB/M3; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ROSIN (CORE FLUX)  
Fraction by Wt: 3.4%

Ingred Name:ALIPHATIC ALCOHOL  
Fraction by Wt: 0.18%

=====  
Hazards Identification  
=====

Effects of Overexposure:FLUX: CAN CAUSE IRRITATION OF SKIN & MUCOUS  
MEMBRANE.

=====  
First Aid Measures  
=====

First Aid:REMOVE VICTIM FROM CONTAMINATED AREA & KEEP EWARM & QUIE  
T IN  
FRESH AIR.

=====  
Fire Fighting Measures  
=====

Flash Point:261F,127C COC  
Extinguishing Media:FLUX:CO\*2, DRY CHEMICAL  
Unusual Fire/Explosion Hazard:IN A FIRE MATERIAL COULD EMIT TOXIC &  
CORROSIVE FUMES.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:FLUX MAY BE WIPED FROM A SURFACE WITH  
ISOPROPYL ALCOHOL & A SPONGE.

=====  
Handling and Storage  
=====

Handling and S  
torage Precautions:USE WITH ADEQUATE LOCAL  
VENTILATION,STORE BELOW 100F,38C.

=====  
Exposure Controls/Personal Protection  
=====

Ventilation:LOCAL EXHAUST  
Supplemental Safety and Health  
ADDTNL INGRED:10017650H ORGANIC HALIDE 0.04%. FL PT IS FOR FLUX.  
MELTING PT:361F,183C. DIMENSIONS:0.063 INCHES DIAMETER; 1 LB.  
SPOOL. FED SPEC:QQ-S-571E.

=====  
Physical/Chemical Properties  
=====

HCC:N1  
Appearance and Odor:ALLOY:DULL SILVER. FLUX:AMBER. W

IRE W/ROSIN CORE.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS

Hazardous Decomposition Products: MAY EVOLVE ACIDS, HALOGENS, AMINES.

===== Disposal Considerations =====

Waste Disposal Methods: IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the De

partment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.