

ENMAR -- 742 408,TT-E-489,M C GREEN ENAMEL GLOSS -- 8010-00-526-1608

=====
Product Identification
=====

Product ID:742 408,TT-E-489,M C GREEN ENAMEL GLOSS

MSDS Date:01/01/1987

FSC:8010

NIIN:00-526-1608

MSDS Number: BFCMJ

=== Responsible Party ===

Company Name:ENMAR

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:OO111

=== Contractor Identification ===

Company Name:AMERON

INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

Company Name:ENMAR

Address:201 N BERRY ST

Box:City:BREA

Phone:(316)-7333-1361

CAGE:OO111

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 49.4%

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overex

posure:INH:ANESTHETIC,IRRIT OF RESP TRACT OR ACUTE CNS
DEPRSSN W/ HDACHE,DIZ,UNCON,COMA. SKIN & EYE:IRRIT

=====
First Aid Measures
=====

First Aid:IN CASE OF CONTACT,FLUSH SKIN & EYES W/PLENTY OF WATER WHILE
REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH AIR.CALL
A PHYSICIAN IF SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point:85F TCC

Lower Limits:1.1

Extinguishing Media:SM FIRES:CO*

2,DRY CHEM.LG FIRES:POLYMER FOAM
PREFERRED

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAME,HOT
SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID
BREATHING VAPORS.VENTILATE AREA.REMOVE W/INERT ABSORBENT &
NON-SPARKING TOOLS

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QTY
IN BUILDINGS DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ.DO NOT TAKE
INTERNALLY.ADD LABEL WARNING.

Other Precautions:GROUND CONTAINERS WHEN POURING.AVOID FREE FALL OF LIQ
IN EXCESS OF FEW IN.DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL
W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.DOT:FLAM LIQUID

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR. CLSD:AIR-LINE TYPE

Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV FUM

Protective Gloves:YES

Eye Protection:YES,FOR SPLASH

Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING

Supplemental Safety and Health

VAPOR PRESSURE:3.2;VAPOR DENSITY: HEAVIER THAN AIR; WT PER GALLON:8.2
LBS.CONFORMS-TO TT-E-489F, CPL,CLA.

=====
Physical/Chemical Properties
=====

====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:63.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES,HEAT & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER.DISPOSE IN
ACCORDANCE W/FED.,STATE & LOCAL REGULATIONS

Disclaimer

(provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.