

H.R.SIMON & CO.,INC. -- S60-0425 CHEM BLEND PHOTO-FIXER, PART 1 -- 6750-00-528-0473

===== Product Identification =====

Product ID:S60-0425 CHEM BLEND PHOTO-FIXER, PART 1

MSDS Date:01/01/1987

FSC:6750

NIIN:00-528-0473

Kit Part:Y

MSDS Number: BFCYS

=== Responsible Party ===

Company Name:H.R.SIMON & CO.,INC.

Address:3515 MARMEMCO CT.

City:BALTIMORE

State:MD

ZIP:21230-3411

Info Phone Num:301-636-5555

Emergency Phone Num:301-636-5555

CAGE:LO524

=== Contractor Identification ===

Company Name:H.R.SIMON & CO.,INC.

Address:3515 MARMEMCO CT.

Box:City:BALTIMORE

State:MD

ZIP:21230-3411

Phone:301-636-5555

CAGE:LO524

Company Name:SIMON H R CO,INC.

Address:3515 MARMENCO COURT

Box:City:BALTIMORE

State:MD

ZIP:21230-3411

Country:US

Phone:410-636-5555

CAGE:27912

===== Composition/Information on Ingredients =====

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

Minumum %

Wt:5.
Maxumum % Wt:10.
Other REC Limits:ACGIH STEL 15 PPM
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM THIOSULFATE
CAS:7783-18-8
RTECS #:XN6465000
Minumum % Wt:40.
Maxumum % Wt:50.

Ingred Name:SODIUM BISULFITE (SASA III)
CAS:7631-90-5
RTECS #:VZ2000000
Minumum % Wt:1.
Maxumum % Wt:5.
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by
Wt: TO 100%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NO EFFECTS KNOWN EXCEPT IRRITATION.
Effects of Overexposure:EYES/SKIN:IRRITATION,BURNING.
Medical Cond Aggravated by Exposure:NONE LISTED BY MFR.

===== First Aid Measures =====

First Aid:EYE/SKIN:FLUSH WITH WATER. GET MEDICAL HELP IF

IRRITATION IS
SEVERE OR PERSISTS. INGESTED/INHALED:GET MEDICAL HELP.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE AGENT APPROPRIATE FOR SURROUNDING FIRE.
Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:POSSIBILITY OF HAZARDOUS PRODUCTS OF
THERMAL DECOMPOSITION.

===== Accidental Release Measures =====

Spill Release Proc
edures:FLUSH WITH WATER TO DRAIN.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:USE NORMAL INDUSTRIAL HYGIENE
PRACTICES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:MFR RECOMMENDS GENERAL VENTILATION,10 RM VOLUMES/HR.
Protective Gloves:NONE
Eye Protection:SAFETY GLASSES / GOGGLES
Supplemental Safety and Health
THIS IS PART 1 OF 2 PART KIT. SEE P/N
IN D, B FOR 2. BOTH ARE REQUIRED
TO BE MIXED TOGEATHER AND DILUTED TO MAKE THE OR 10 GAL PAPER
FIXER.KEY1:C2.

===== Physical/Chemical Properties =====

HCC:C2
Boiling Pt:>100.C, 212.F
Vapor Pres:18 MM
Vapor Density:0.6
Spec Gravity:1.33
pH:5.0
Solubility in Water:COMPLETE
Appearance and Odor:COLORLESS LIQUID, SLIGHT AMMONIA ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ALKALI
Stab

ility Condition to Avoid:NONE STATED BY MFR
Hazardous Decomposition Products:FREE AMMONIA

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accu
rate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.