

TURCO PRODUCTS,INC. -- TURCO 2822 THICK -- 6850-00-530-5241

===== Product Identification =====

Product ID:TURCO 2822 THICK

MSDS Date:01/01/1985

FSC:6850

NIIN:00-530-5241

MSDS Number: BFDBK

=== Responsible Party ===

Company Name:TURCO PRODUCTS,INC.

Address:24700 SOUTH MAIN STREET

Box:6200

City:CARSON

State:CA

ZIP:90749

Country:US

Info Phone Num:714-890-3600

Emergency Phone Num:614-387-6200

CAGE:D98

08

=== Contractor Identification ===

Company Name:TURCO PRODUCTS, INC. DIVISON OF ELF ATOCHEM NORTH AMERICA

Address:2000 MARKET ST

Box:City:PHILADELPHIA

State:PA

ZIP:19103-3222

Country:US

Phone:215-419-7890

CAGE:61102

Company Name:TURCO PRODUCTS,INC.

Box:6200

City:PHILADELPHIA

State:PA

ZIP:19103

Country:US

Phone:215-419-7890

CAGE:D9808

===== Composition/Information on Ingredients =====

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 81.

4%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETIC ACID (SARA III)
CAS:64-19-7
RTECS #:AF1225000
Fraction by Wt: 11.4%
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ALKYLARYL SULFONATE,SODIUM SALT
Fraction by Wt: 3.47%

Ingred Name:HYDROXYPROPYL METHYL CELLULOSE
CAS:9004-64-2
RTECS #:NF9050000
Fraction by Wt: 1.50%

Ingred Name:PARAFFIN WAX
CAS:8002-74-2
RTECS #:RV0350000

Fraction by Wt: 1.0%

===== Hazards Identification =====

Effects of Overexposure:INH:DIZZ,HEAD,RESP IRRIT;SKIN:IRRIT,MAY CAUSE
BLISTERS/ABSORB TOXIC AMTS.EYES:SEV IRRIR,DAMAGE TISSU

===== First Aid Measures =====

First Aid:SKIN:WASH W/SOAP & WATER,GET MD IF IRRIT/BLISTERING
OCCURS;EYES:FLUSH W/LG VOL OF WATER FOR 15 MIN;INH:REMOVE TO FRESH
AIR.GIVE CPR/OXY IF NEEDED;ING:DO NOT INDUCE VOMIT.DILUTE BY GIVING

MILK/WATER;GE T MED ATTN IMMED FOR ANY PROBLEM.*SEE OTHER PRECAU

===== Fire Fighting Measures =====

Flash Point:NONE

Lower Limits:UNK

Upper Limits:UNK

Extinguishing Media:CO*2,FOAM

Fire Fighting Procedures:USE SELF-CNTND BRTHNG APP.DO NOT USE CANISTERS
W/HOPCALITE.

Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION MAY PRODUCE TOXIC
OXIDES OF CARBON & CHLORINE.

===== Accidental Release Measures =====

Spill Release Proce

dures:VENTILATE AREA.WEAR PROTECTVE EQUIP.ELEMINATE

IGN SOURCE.STOP LEAK W/O RISK.DIKE/CONTAIN SPILLAGE.WIPE UP OR
ABSORB SPILLAGE ONTO ABSORBENT MATL.RECOVER IN DRUMS/CONTNRS WHICH
ARE SUITABLE FOR SHIPMEN T TO DISPOSAL LOCATION.

===== Handling and Storage =====

Handling and Storage Precautions:TRANSPORT & STORE IN CLOSED CONTAINERS
AT TEMPERATURES BELOW 90F.USE CARE IN OPENING DRUMS TO AVOID
SPURTING OF CONTENTS.

Other Precautions:NOTE:T

O PHYSICIAN:POST STERNUM CHEST PAIN MAY

INDICATE ACCUM OF DANG LEV OF CARBOXY HEMOGLBN;EFFECTS OF
OVEREXPOSURE,ACUTE:MAY CAUSE ACCUM OF CARBOXYL HEMOGLBN.MAY LEAD TO
ANESTHESIA/NORCOSIS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CANISTER TYPE MASK W/ORGANIC VAP CARTRIDGE;NEVER
USE CANST W/HOPCLIT

Ventilation:MECHANICAL VENTILATION(LOCAL EXHAUST)

Protective Gloves:NEOPRENE

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment

:SOLVENT RESISTANT BOOTS & APRON

Supplemental Safety and Health

HAZ INGRD:BALANCE OF MIXTURE CONTAIN:COMPLEX FATTY

AMINESALT-0.5%;MERCAPTOBENZOTHTIOZOLE-0.02%;WALNUT BROWN

L.S.719(DYE)-0.01%;WATER-0.70%

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:APPROX,105F

Vapor Pres:300

Vapor Density:>1.0

Spec Gravity:1.26

Evaporation Rate & Reference: