

BULK CHEMICALS DISTRIBUTORS,INC -- CORROSION PREVENTIVE COMPOUND, TY III --
8030-00-546-8637

=====
Product Identification
=====

Product ID:CORROSION PREVENTIVE COMPOUND, TY III
MSDS Date:01/01/1985
FSC:8030
NIIN:00-546-8637
MSDS Number: BFDTX
=== Responsible Party ===
Company Name:BULK CHEMICALS DISTRIBUTORS,INC
Address:80 FIRST STREET
City:GRETNA
State:LA
ZIP:70053
Country:US
Info Phone Num:800-
535-4095(OTHER COMPANY), O.O.B.
Emergency Phone Num:504-362-3232 DISCONNECTED(2-20-92)
CAGE:56921

==== Contractor Identification ===
Company Name:BULK CHEMICALS DISTRIBUTORS,INC
Address:80 FIRST STREET
City:GRETNA,
State:LA
ZIP:70053
Country:US
Phone:504-362-3232 DISCONNECTED(2-20-92)
CAGE:56921

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT 140, HI-FLASH ALIPHATIC HYDROCARBON BLEND
Fraction by Wt: 80%
ACGIH TLV:25 PPM, MFR

Ingred Name:INHIBITOR BLEND(
INCLUDES BARIUM SOAP OF AN OXYGENATED
HYDROCARBON)
Fraction by Wt: 20%

Ingred Name:BARIUM SOAP OF AN OXYGENATED HYDROCARBON

=====
Hazards Identification
=====

Effects of Overexposure:VAPORS MIGHT AFFECT CENTRAL NERVOUS SYSTEM &
CAUSE RESPIRATORY IRRITATION.

=====
First Aid Measures
=====

First Aid:SKIN:WASH W/SOAP & WATER. AN EMOLLIENT CREAM OR LOTION IS
BENEFICIAL. EYES:WASH W/PLENTY OF WATER 15 MINS. INH:P

PROVIDE FRESH

AIR & REST. ING:DO NOT INDUCE VOMITING. CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:163F,73C COC

Extinguishing Media:MECHANICAL FOAM, DRY CHEMICAL, WATER FOG, CO*2

Fire Fighting Procedures:STRAIGHT WATER STREAM WOULD SPREAD OIL FIRES.

Unusual Fire/Explosion Hazard:VAPOR ACCUMULATION WOULD FLASH &/OR
EXPLODE IF IGNITED.

=====
Accidental Release Measures
=====

Spill Release Procedures:AVOID OPEN FLAM

E. PROVIDE ADEQUATE

VENTILATION. COLLECT & DISPOSE OF ALL SPILLED LIQUID.

=====
Handling and Storage
=====

Handling and Storage Precautions:HANDLE AS A COMBUSTIBLE LIQUID.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:INADEQUATE VENT:SCBA. OTHER:NIOSH/MSHA APPRVD
FOR EXPOS OF CONCERN.

Ventilation:LOCAL EXHAUST TO A FIRE SAFE AREA.

Protective Gloves:RECOMMENDED

Eye Protection:RECOMMENDED

Other Protective E

quipment:AS REQUIRED TO AVOID WETTING CLOTHES.

Supplemental Safety and Health

CONFORMS TO MIL-C-81309D, TY III. CONTAINER SIZE:16 OZ AEROSOL CAN. VAP
PRESS:0.5-2.3.

=====
Physical/Chemical Properties
=====

HCC:V2

Boiling Pt:B.P. Text:390F,199C

Vapor Density:6.2

Spec Gravity:0.835

Evaporation Rate & Reference:0.05, N-BUAC

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK AMBER W/ORGANIC ODOR

Percent Volatiles by Volume:20

=====
Stability a

nd Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE

Hazardous Decomposition Products: NONE

===== Disposal Considerations =====

Waste Disposal Methods: THIS IS AK COMBUSTIBLE HYDROCARBON & WILL BURN IF IGNITED. USE THE SAME PRECAUTIONS FOR DISPOSAL AS YOU WOULD KEROSENE OR DIESEL OIL. DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.