View NSN Online: https://aerobasegroup.tw/nsn/6850-00-703-7406

Product ID:TRACER TECH D495C DEVELOPER

MSDS Date:04/01/1983

FSC:6635

NIIN:00-703-7406

MSDS Number: BFLYZ === Responsible Party === Company Name:ARDROX INC Address:16961 KNOTT AVE

City:LA MIRADA

State:CA

ZIP:90638-6015 Country:US

Info Phone Num:714-739-2821

Emergency Phone Num:714-739-2821

CAGE:23373

==

= Contractor Identification ===

Company Name: BRENT AMERICA, INC.

Address:16961 KNOTT AVE.

Box:City:LA MIRADA

State:CA

ZIP:90638-6015 Country:US

Phone:714-739-2821

CAGE:23373

======= Composition/Information on Ingredients ========

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000 Fraction by Wt: 51%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1

Ingred Name:

Ingred Name:SILICA, AMORPHOUS, DUST CAS:112945-52-5 RTECS #:VV7310000 Fraction by Wt: 0.4% OSHA PEL:6 MG/M3 ACGIH TLV:10 MG/M3; 8990
Ingred Name:METHYLENE CHLORIDE (SARA III) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 29% OSHA PEL:500 PPM/C,1000; Z2 ACGIH TLV:50 PPM, A2; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
============= Hazards Identification ==============
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carci nogenicity:NTP:NO IARC:NO OSHA:NO Effects of Overexposure:ANAESTHETIC EFFECTS,HEADACHES,NAUSEA.
======================================
First Aid:EYE:FLUSH W/COPIOUS AMOUNT OF WATER;SKIN: WASH WITH SOAP & WATER;INHALE:REMOVE TO FRESH AIR,GIVE ARTIFICIAL RESPIRATION IF NEEDED;INGEST:DO NOT INDUCE VOMITING,CALL PHYSICIAN.
======================================
Flash Point:NONE Extinguishing Media:CO2, FOAM, DRY CHEM. Fire Fi ghting Procedures:NONE Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ==========
Spill Release Procedures:USE ABSORBENT MINERAL GRANULES,SAND OR EARTH TO REMOVE MAJORITY OF SPILLAGE. MOP UP USING A DETERGENT ANY POWDER REMAINING.
============ Handling and Storage =============
Handling and Storage Precautions:STORE AEROSOLS OUT OF DIRECT SUNLIGHT.
====== Exposure Controls/Personal Protection =======
Res

POWER CONTENT Fraction by Wt: 10%

Ventilation:LOCAL EXHAUST Protective Gloves:NONE Supplemental Safety and Health KIT HAD 4 PARTS: P-149 PENETRANT, D-495C & D-493A DEVELOPERS, AND K410C REMOVER. THE KIT IS MARKETED BY THE COMPANY WHICH CHANGED NAME TO "ARDROX INC". PROPELLANT IN THE CAN WAS MIXTURE OF ISOBUTANE/PRO PANE GAS. KEY1:F1. CURRENT KIT HAS ESSENTIALLY THE SAME PARTS.THIS IS D495C, FSC 6635 FOR THIS PRODUCT IS NOW FSC 6850. ======= Ph vsical/Chemical Properties ========= Boiling Pt:B.P. Text:>104F/46C Vapor Pres:100 Spec Gravity:1.4 Solubility in Water: NEGLIGIBLE Appearance and Odor:SUSPENSION OF WHITE POWDER IN LIQUID. Percent Volatiles by Volume:60.0 ======== Stability and Reactivity Data ========== SLOW HYDROLYSIS PRODUCES CORROSIVE ACID Stability Condition to Avoid: OPEN FLAMES Hazardous Decomposition Products: EXPOSURE TO HIGH TEMP.OR OPEN FLAME GENERATES HCL & PHOSG,CL Conditions to Avoid Polymerization: OPEN FLAMES. WELDING ARCS ======= Disposal Considerations ============== Waste Disposal Methods: USE SPECIALIST WASTE DISPOSAL COMPANY. FOR SMALL QUANTITIES, ALLOW SOLVENT TO EVAPORATE OUTSIDE THEN SWEEP UP POWDER REMAINING AND PUT IN TRASH. Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

piratory Protection: NO SPECIAL PROTECTIVE CLOTHING REQUIRED

of Defense. The United States of America in no manner whatso ever.

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.