View NSN Online: https://aerobasegroup.tw/nsn/6685-00-741-2564 AC SPARK PLUG DIVISION, GENERAL MOTORS CORP -- 1507825 -- 6685-00-741-2564 Product ID:1507825

MSDS Date:01/01/1985

FSC:6685

NIIN:00-741-2564

MSDS Number: BFMWR === Responsible Party ===

Company Name: AC SPARK PLUG DIVISION, GENERAL MOTORS CORP

Address:1300 N DORT HWY

City:FLINT State:MI ZIP:48556 Country:US CAGE:61928

=== Contractor Identification ===

Company Name

:GENERAL MOTORS CORP AC SPARK PLUG DIV

Address:1300 N DORT HWY

Box:City:FLINT

State:MI ZIP:48556 Country:US CAGE:70040

Company Name: GENERAL MOTORS CORP AC-DELCO DIV

Address:6060 W BRISTOL RD

Box:City:FLINT

State:MI ZIP:48554 Country:US

Phone:810-635-5905

CAGE:61928

======= Composition/Information on Ingredients ========

Ingred Name: RADIUM 226 (1.224UCI)

============ Hazards Identification =========================

Effects of Overexposure: HAZARD DEGREE DEPENDS ON THE TYPE

| AND QUANTITY OF RADIATION. LATENT EFFECTS: SOMATIC/GENETIC DAMAGE. |
|--|
| ====================================== |
| First Aid:USE FIRST AID. CALL MEDICAL EMERGENCY CARE. REMOVE AND ISOLATE COMTAMINATED CLOTHING. SHOWER VICTIM WITH SOAP AND WATER. DETAIN PERSONNEL AND EQUIPMENT EXPOSED. ADVISE MEDICAL PERSONNEL THAT VICTIM MAY BE CONTAMINATED. |
| ====================================== |
| Extinguishing Media:EXTINQUISH WITH AGENT SUI TABLE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:SOME OF MATERIAL MAY BURN. CONTAINERS MAY EXPLODE IN HEAT OF FIRE. |
| ====================================== |
| Spill Release Procedures:HANDLE BROKEN DEVICE WITH GLOVES AND FORCEPS. |
| ====================================== |
| Handling and Storage Precautions:SHIELD ACCORDING TO EMI TTED RADIATION. PROTECT FROM FILM AND FILM PLATES. KEEP CONTAINERS CLOSED. STORE IN AREA FOR RADIOACTIVE MATERIALS. |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:SELF CONTAINED BREATHING APPARATUS IF INVOLVED IN FIRE, OTHERWISE GAS MASK. Ventilation:PROVIDE MECHANICAL (GENERAL/LOCAL EXHAUST) VENTILATION TO MAINTAIN < TLV. Protective Gloves:IMPERVIOUS |

Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYE WASH STATION, APRONS, S

| CLOTHING |
|--|
| Supplemental Safety and Health |
| SAFETY AND HEALTH DATA DEVELOPED BY DGSC-STH. ISOTOPE AND ACTIVITY |
| PROVIDED BY AC SPARK PLUG DIV OF GENERAL MOTORS THRU US ARMY |
| AVIATION SYSTEMS COMMAND. SEE DGSC-STH CASE NO. 85241V. ITEM |
| CONTAINS 1. 224 UCI OF RADIUM 226. |
| |
| ====================================== |
| HCC:A3 |
| HOC.AS |
| ========= Stability and Reactivity Data ========== |
| |
| Stability Indicator/Materials to Avoid:YES |
| ICOLATE AND |

PECIAL IMPERVIOUS

ISOLATE AND
SEGREGATE FROM MOST OTHER TYPE MATERIAL.
Hazardous Decomposition Products:DEPENDS ON CHEMICAL COMPOSITION;
FISSION PRODUCTS

======= Disposal Considerations ===========

Waste Disposal Methods:CONTROLLED DISPOSAL REQUIRED IN ACCORDANCE WITH DOD REGULATIONS AND FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.