

GENERAL ELECTRIC CO. -- SS-4120 PRIMER -- 8040-00-814-1125

=====
Product Identification
=====

Product ID:SS-4120 PRIMER

MSDS Date:01/01/1985

FSC:8040

NIIN:00-814-1125

MSDS Number: BFQMZ

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO.

Address:HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Emergency Phone Num:518-237-3330

CAGE:01139

=== Contractor Identification ===

Comp

any Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 50%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 44%

OSHA PEL:S,200PPM

/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL SILICATE
CAS:78-10-4
RTECS #:VV9450000
Fraction by Wt: 6%
OSHA PEL:100 PPM
ACGIH TLV:10 PPM; 9293

===== Hazards Identification =====

Effects of Overexposure:EYE IRRITATION.SKIN DRYING ACTION.
INHALATION:HEADACHE DIZZINESS AND NAUSEA.

===== First Aid Measures =====

First Aid:EYE CONT:FLUSH W/WATER 15 MIN,CALL MD.SKIN C
ONT:WASH WITH
MILD SOAP AND WATER,APPLY SKIN CREAM.INHALATION:REMOVE TO FRESH
AIR.IF INGESTED,INDUCE VOMITING,CALL DR.

===== Fire Fighting Measures =====

Flash Point:31F TCC
Lower Limits:4.3
Upper Limits:36
Extinguishing Media:WATER SPRAY,CO*2,FOAM,DRY CHEMICAL

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB IN SAND OR INERT ABSORBENT AND PLACE IN
A METAL CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEATED SURFACES,SPARKS
AND OPEN FLAMES.AVOID PROLONGED OR REPEATED SKIN CONTACT.AVOID
EXCESS IR PROLONG INHALATION OF VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN
Ventilation:LOCAL EXHAUST
Protective Gloves:YES
Eye Protection:SAFETY GLASSES
Other Protective Equip

ment:EYE BATH,SAFETY SHOWER
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:150-175F
Vapor Pres:96
Vapor Density:1.4
Spec Gravity:0.82
Evaporation Rate & Reference:BUAC 2-3.5
Solubility in Water:SOLUBLE
Appearance and Odor:COLORLESS LIQUID,ALCOHOL ODOR.
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING
AGENTS
Stability Condition to Avoid:HEAT,SPARKS AND OPEN FLAME
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY RELEASE SIOZ
AND CO*2

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER SAME CONDITIONS,OR DISPOSE IN A
LEACHPROOF LANDFILL.FEDERAL STATE AND LOCAL LAWS APPLY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.