

CON-LUX COATINGS,INC. -- ENAMEL,ALKYD,GLOSS 15123 -- 8010-00-853-1859

=====
Product Identification
=====

Product ID:ENAMEL,ALKYD,GLOSS 15123

MSDS Date:01/01/1987

FSC:8010

NIIN:00-853-1859

MSDS Number: BFSTJ

=== Responsible Party ===

Company Name:CON-LUX COATINGS,INC.

Address:226 TALMADGE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-287-4000

Emergency Phone Num:20

1-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 50.8%

OSHA PEL:100 PPM

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: > 1%

OSHA PEL:15 MG/M3 TDUST

A

CGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ODORLESS MINERAL SPIRITS
(VAPOR PRESSURE 2.00 MM HG @ 20C)

CAS:64741-65-7

OSHA PEL:500 PPM

===== Hazards Identification =====

Effects of Overexposure:IRRITATION OF EYES AND SKIN.IRRITATION OF
RESPIRATORY TRACT.HEADACHE OR DIZZINESS.

===== First Aid Measures =====

First Aid:SKIN/EYE:FLUSH WITH WATER. INHAL:MOVE TO FRESH AIR. IF
IRRITATION PERSISTS CALL DR.

===== Fire Fighting Measures =====

Flash Point:40.6/105 TCC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CLASS B EXTINGUISHERS (CO*2,DRY CHEM.OR FOAM)

Fire Fighting Procedures:USE WATER TO COOL CLOSED CONTAINERS & PREVENT
AUTOIGNITION

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED AND
ISOLATE FROM SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOUCES
OF IGNITION(FLAMES,HOT

SURFACES,ELECTRICAL,STATIC OR FRICTIONAL SPARKS)AVOID BREATHING OF
VAPORS.VENTILATE AREA.REMOVE WITH NON-SPARKING TOOLS AND INERT
ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMP. KEEP
AWAY FROM OPEN FLAME AND SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED
WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

=====

= Exposure Controls/Personal Protection =====

Respiratory Protection:BUREAU OF MINES APPROVED CHEM./MECH FILTER
RESPIRATOR

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:SAFETY GOGGLES OR GLASSES

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH
CONTAMINATED CLOTHING

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:157.2/315

Vapor Pres:1

Vapor Density:4.7

Spec Gravity:

1.02

Evaporation Rate & Reference:BUAC=1: 0.15

Solubility in Water:0

Appearance and Odor:BLUE LIQUID,MILD ALIPHATIC ODOR.

Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND
FEDERAL REGULATIONS.DO NOT INCINERATE CLOSED C
ONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
partic

ular situation.