

CHEMRAY COATINGS CORPORATION -- TT-P-115E,TV2,PAINT,TRAFFIC,WHITE -- 8010-00-900-2938

===== Product Identification =====

Product ID:TT-P-115E,TV2,PAINT,TRAFFIC,WHITE  
MSDS Date:01/01/1987  
FSC:8010  
NIIN:00-900-2938  
MSDS Number: BFVKF  
=== Responsible Party ===  
Company Name:CHEMRAY COATINGS CORPORATION  
Address:209 MICHIGAN AVE.  
City:KENILWORTH  
State:NJ  
ZIP:07033  
Country:US  
Emergency Phone Num:201-245-1111  
CAGE:OBRN9  
=== Contractor Identification ===  
Company Name:CHEMRAY COATING CORP  
Address:209 N MICHIGAN AVE  
Box:City:KENILWORTH  
State:NJ  
ZIP:07033  
Country:US  
Phone:201-245-1111  
CAGE:33832  
Company Name:CHEMRAY COATINGS CORP.  
Address:209 N. MICHIGAN AVE.  
Box:NA  
City:KENILWORTH  
State:NJ  
ZIP:07033  
Country:US  
Phone:800-924-9300  
CAGE:OBRN9

===== Composition/Information on Ingredients =====

Ingred Name:PIGMENTS (50 TO 53% OF PRODUCT)

Ingred Name:VINYL TOLVENE BUTADIENE (AS VEHIC

LE)(47 TO 50% OF PRODUCT)

Ingred Name:SOLVENTS (TYPE NOT SPECIFIED)(33 TO 34% OF PRODUCT)

Ingred Name:ADDITIVES (0.5 TO 1% OF PRODUCT)

===== Hazards Identification =====

Effects of Overexposure:INHALATION CAUSES DIZZINESS.

===== First Aid Measures =====

First Aid:INHALATION:MOVE TO FRESH AIR. EYE:IMMEDIATELY FLUSH W/WATER  
FOR AT LEAST 15 MIN.

===== Fire Fighting Measures =====

FI  
ash Point:55 F PMCC  
Extinguishing Media:CO\*2  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURESOVER 150F  
BECAUSE OF EXPANSION OF CONTANER CONTENTS.  
Other Precautions:DO NOT FREEZE. DOT CLASSIFICATION:COMBUSTIBLE. WASH  
HANDS THOROUGHLY AFTER HA  
NDLING PRODUCT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP. PROT. FOR PARTICULAR  
EXP. OF CONCERN  
Ventilation:USE MECHAICAL, PROVIDE ADEQUATE LOCAL EXHAUST.J  
Eye Protection:GOGLES IF SPRAYING  
Supplemental Safety and Health  
PERCENT VOLATILE BY VOLUME: 57.5 TO 58.5%

===== Physical/Chemical Properties =====

HCC:F3  
Boiling Pt:B.P. Text:320 F  
Spec Gravity:1.29  
Evaporation Rate & Reference:1

.2 TOLVENE

Appearance and Odor:WHITE PAINT, NOT OBNOXIOUS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:NO UNUSUAL REQUIREMENTS. DISPOSE IN ACCORDANCE  
W/LOCAL,STATE & FEDERA REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of De

fense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.