

PACIFIC AEROSOL, INC. -- MIL-C-16173D AEROSOL COATING COMPOUND -- 8030-00-903-0931
===== Product Identification =====

Product ID:MIL-C-16173D AEROSOL COATING COMPOUND

MSDS Date:01/01/1985

FSC:8030

NIIN:00-903-0931

MSDS Number: BFVRP

=== Responsible Party ===

Company Name:PACIFIC AEROSOL, INC.

Address:2424 MERCED ST.

Box:2112

City:SAN LEANDRO

State:CA

ZIP:94577-4211

Country:US

CAGE:34451

=== Contr

actor Identification ===

Company Name:AERVOE-PACIFIC CO, INC.

Address:1198 SAWMILL RD

Box:City:GARDNERVILLE

State:NV

ZIP:89410

Country:US

Phone:(702)-782-0100

CAGE:33451

Company Name:PACIFIC AEROSOL, INC.

CAGE:34451

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 18.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL CELLOSOLVE ACETATE

(2-BUTOXYETHANOL ACETATE)

CAS:112-07-2

RTECS #:KJ8925000

Fraction by Wt: 20.0%

ACGIH TLV:200 PPM

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 42.0%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 20.0%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

=====

===== Hazards Identification =====

Effects of Overexposure:POSSIBLE HEADACHES, DIZZINESS, EYE IRRITATION AND RESPIRATORY IRRITATION.

===== First Aid Measures =====

First Aid:INHALATION: MOVE TO FRESH AIR, RESTORE BREATHING, IF NECESSARY, & CALL PHYSICIAN. EYE CONTACT: FLUSH EYES THOROUGHLY WITH WATER; GET MEDICAL AID.

===== Fire Fighting Measures =====

Flash Point:-19 C

Lower Limits:1.00

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE ON FIRE.
Unusual Fire/Explosion Hazard:AVOID HEAT, SPARKS, AND FLAME. CLOSED
CANS CAN EXPLODE IF EXPOSED TO EXTREME HEAT. COOL W/H2O SPRAY

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION; VENTILATE AREA.

===== Handling and Storage =====

Handling and Storage Precautions:STO
RE BELOW 120F. KEEP CONTAINERS AWAY
FROM HEAT AND OPEN FLAME.

Other Precautions:AVOID INHALATION OF SPRAY MISTS. DO NOT TAKE
INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PAINT SPRAY MASKS, ETC.
Ventilation:PROVIDE EXHAUST VENTILATION TO KEEP BELOW TLV.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3
Boiling Pt:B.P. Text:-10F
Spec Gravity:0.9000

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
CONTAINERS ARE PRESSURIZED - AVOID EXTREME HEAT.
Hazardous Decomposition Products:CO ON IGNITION.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE IN
ACCORDANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the D

epartment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.