View NSN Online: https://aerobasegroup.com/nsn/8040-00-914-6970

DOW CORNING CORPORATION -- 1200 RTV PRIME COAT-RED -- 8040-00-914-6970

Product ID:1200 RTV PRIME COAT-RED MSDS Date:01/01/1987 FSC:8040 NIIN:00-914-6970 MSDS Number: BFWGR === Responsible Party === Company Name: DOW CORNING CORPORATION Address:3901 SOUTH SAGINAW ROAD Box:997 City:MIDLAND State:MI ZIP:48640 Country:US Info Phone Num:517-496-5900 **Emergency Phone Nu** m:517-496-5900 CAGE:5D028 === Contractor Identification === Company Name: DOW CORNING CORP Address:3901 S SAGINAW RD Box:997 City:MIDLAND State:MI ZIP:48686-0997 Country:US Phone:517-496-6000/517-496-6315 CAGE:5D028 Company Name: DOW CORNING CORP Address:2200 W SALZBURG RD Box:City:AUBURN State:MI ZIP:48611 Country:US Phone:517-496-4388 CAGE:71984

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: >80% OSHA PEL:100 PPM

======================================
Effects of Overexposure:BURNS SKIN AND EYES. SLIGHT HEADACHES, ANESTHESIA.
======================================
First Aid:INHALATION: REMOVE TO FRESH AIR. CONSULT PHYSICIAN. SKIN AND EYES: FLUSH WITH WATER.
======================================
Flash Point:50F CC Lower Limits:0.2 Upper Limits:6.0 Extinguishing Med ia:CO*2 OR FOAM
======================================
Spill Release Procedures: MOP, WIPE OR SOAK UP WITH ABSORBENT MATERIAL USING PROPER PROTECTIVE EQUIPMENT
======================================
Handling and Storage Precautions:SAME AS FOR ANY OTHER FLAMMABLE PRODUCT. USE REASONABLE CARE.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:ORANIC VAPOR TYPE-NIOSH/MSHA APPROVED RESPIR ATOR Ventilation:MECHANICAL VENTILATION RECOMMENDED. Protective Gloves:RUBBER/PLASTIC Eye Protection:SAFETY GLASSES Other Protective Equipment:AS LOCAL REGULATIONS MAY REQUIRE. Supplemental Safety and Health % VOLATILE IS >50%. SIZE - QUART
======================================
HCC:F3 NRC/State Lic Num:NA Boiling Pt:B.P. Text:210F Vapor Pres:25 Vapor Density:1.0 Spec Gravity:0.9 Evaporation Rate & amp; Reference:1.0 ETHER Solubility in Water:SLIGHT Appearance and

Odor:LIQUID. SOLVENT ODOR.

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIAL Hazardous Decomposition Products:METAL OXIDES, CO:2 & PARTIALLY BURNED CARBON PRODUCTS.

Waste Disposal Methods:REFER TO LOCAL, STATE AND FEDERAL REGULATIONS PERTAINING TO SOLVENT DISPOSAL

Disclaimer (provided with this information by the compiling agencies):

his information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.