

OCTAGON PROCESS,INC. -- UNIVOLT 60-1830 -- 9160-00-926-2124

===== Product Identification =====

Product ID:UNIVOLT 60-1830

MSDS Date:01/01/1987

FSC:9160

NIIN:00-926-2124

MSDS Number: BFWTM

=== Responsible Party ===

Company Name:OCTAGON PROCESS,INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Info Phone Num:201-945-9400

Emergency Phone Num:201-945-9400

CAGE:DO973

=== Contract

or Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

Company Name:OCTAGON PROCESS,INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Phone:201-945-9400

CAGE:DO973

===== Composition/Information on Ingredients =====

Ingred Name:COMPLEX MIXTURE OF PETROLEUM HYDROCARBONS.(PER MSDS,PRODUCT
DOES NOT CONTAIN ANY PCB'S)

Other REC Limits:5MG/CUM,AS OI

L MIST

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:SKIN IRRITATION ON PROLONGED CONTACT;OIL MIST,MAY CAUSE RESPIRATORY IRRITATION OR EYES IRRITATION. CHRONIC:NOT KNOWN.

Explanation of Carcinogenicity:NOT SPECIFIED

Medical Cond Aggravated by Exposure:NO DATA IS AVAILABLE

===== First Aid Measures =====

First Aid:SKIN:WASH W.SOAP

& H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T

INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:320F/160C

Lower Limits:1

Upper Limits:7

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*2O SPRAY TO COOL

CONTR.

Unusual Fire/Explosion Hazard:DO NOT MIX WITH OR STORE NEAR STRONG OXIDIZERS.LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK.

EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

===== Handling and S

torage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE
RISK AREA. PROTECT CONTRS FROM PHYS DAMAGE.KEEP OUT OF DIR RAYS OF
SUN AWAY FR ORG PROD & OTHER EASILY OXID MATL

Other Precautions:AVOID BREATHING OIL MIST.REMOVE CONTAMINATED
CLOTHING,LAUNDER BEFORE RE-USE.DISCARD OIL SOAKED SHOES.WASH WITH
SOAP & WATER AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SCBA IN ENCLOSED
AREAS.

Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:EYE WASH STATION. APRONS. SPECIAL IMPERVIOUS
CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:550F/288C

Vapor Pres: