

EXXON COMPANY -- 5114 EP GREASE -- 9150-00-935-4017

===== Product Identification =====

Product ID:5114 EP GREASE

MSDS Date:01/01/1985

FSC:9150

NIIN:00-935-4017

MSDS Number: BFXNT

=== Responsible Party ===

Company Name:EXXON COMPANY

Emergency Phone Num:713-656-3424

CAGE:72447

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:U

S

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, U.S.A.

Address:ROOM 2344

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949

CAGE:72447

===== Composition/Information on Ingredients =====

Ingred Name:LITHIUM SOAP

Ingred Name:SYNTHETIC ESTERS

===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN:IRRITATION.INJECTION OF GREASE INTO
SKIN:SOFT TISSUE DAMAGE.

=====

=====
First Aid Measures
=====

First Aid:EYE:FLUSH WITH WATER 15 MINUTES. SKIN:WASH WITH SOAP & WATER.
INJECTION OF GREASE INTO SKIN:SOFT TISSUE DAMAGE.

=====
Fire Fighting Measures
=====

Flash Point:415F/212C (COC)

Lower Limits:1

Upper Limits:7

Extinguishing Media:FOAM,DRY CHEMICAL, CO*2,WATER FOG OR SPRAY.

Fire Fighting Procedures:SELF-CONT BREATH APP,WATER SPRAY TO COOL
EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDANTS

=====
Accidental Release Measures
=====

Spill Release Procedures:RECOVER FREE LUBRICANT. ADD ABSORBENT TO SILL
AREA. KEEP PETROLEUM PRODUCTS OUT OF SEWERS & WATER COURSES BY
DIKING IMPOUNDING.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.

DO NOT HANDLE OR STORE NEAR HEAT, SPARKS,FLAME, OR STRONG OXIDANTS.

Other Precautions:AVOID

BREATHING OIL MIST. LAUNDRER OIL SOAKED CLOTHING
BEFORE REUSE. DISCARD LUBRICANT-SOAKED SHOES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN

Ventilation:LOCAL

Protective Gloves:CHEM RESISTANT

Eye Protection:SPLASH GOGGLE/FACE SHIELD

Other Protective Equipment:CHEM RESISTANT APRON,COVERALLS

Supplemental Safety and Health

CONTAINER SIZE: 14 OZ CART

=====
Physical
=====

I/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>500F/260C

Vapor Density:>10

Spec Gravity:0.94

Evaporation Rate & Reference: