

AMERON INDUSTRIAL COATINGS DIVISION -- 794-104 -- 8010-00-935-7062
===== Product Identification =====

Product ID:794-104
MSDS Date:01/01/1987
FSC:8010
NIIN:00-935-7062
MSDS Number: BFXTN
=== Responsible Party ===
Company Name:AMERON INDUSTRIAL COATINGS DIVISION
Address:201 N BERRY ST
City:BREA
State:CA
ZIP:92621-3904
Country:US
Info Phone Num:714-529-4597
Emergency Phone Num:714-529-4597
CAGE:098
69

=== Contractor Identification ===
Company Name:AMERON INDUSTRIAL COATINGS DIVISION
Address:201 N BERRY ST
Box:City:BREA
State:CA
ZIP:92621-3904
Country:US
Phone:714-529-4597
CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 3.9%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL64750

00

Fraction by Wt: 26.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 12.4%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 22.7%

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 0.7%

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

===== Hazards Identification =====

Effects of Overexposure:INHALE:ANESTHETIC,IRRITATION OF RESPIRATORY TRACT,ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY

===== First Aid Measures =====

First Aid:INCASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER

WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST

=====
===== Fire Fighting Measures =====

Flash Point: 45F, 7C TCC

Lower Limits: 1.0

Extinguishing Media: CARBON DIOXIDE/ DRY CHEMICAL-SMALL; POLYMER
FOAM-LARGE FIRE

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS AVAILABLE
FOR FIREMEN

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD UP

=====
===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT
SURFACES, AND ELECTRICAL, STATIC, OR FRICTIONAL SPARKS) AVOID BREATHING
VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING
TOOLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA

CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID

Other Precautions: DO NOT TAKE INTERNALLY, CONTAINERS SHOULD BE GROUNDED
WHEN POURING, AVOID FREE FALL IN EXCESS OF A FEW INCHES, DO NOT FLAME
CUT, BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: APPROVED BUREAU OF MINES RESPIRATORS W/ PROPER
FILTER OR HOOD

Ventilation: GENERAL DILUTION/ LOCAL EXHAUST FOR TLV & LEL SAFETY & WELDING

Protective Gloves: A LOT OF CONTACT

Eye Protection: USE EYEWEAR IF SPLASHING

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING

Supplemental Safety and Health

BP 79-153C. EFFECTS OF

OVEREXPOSURE- HEADACHE, DIZZINESS ETC. OR COMA. PRIMARY IRRITATION FOR
SKIN OR EYE CONTACT

=====
===== Physical/Chemical Properties =====

HCC: F2

Boiling Pt: B.P. Text: 174-308F

Evaporation Rate & Reference: