View NSN Online: https://aerobasegroup.tw/nsn/6750-00-965-4580

EASTMAN KODAK COMPANY -- 186 2804, VERSMAT FIXER & REPL, TYPE A, PART A -- 6750-00-965-4580

============= Product Identification ==================

Product ID:186 2804, VERSMAT FIXER & REPL, TYPE A, PART A

MSDS Date: 08/05/1982

FSC:6750

NIIN:00-965-4580

MSDS Number: BFZTF === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE ST City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num: NEAREST KODAK

MARKET & DISTRIB CTR

Emergency Phone Num: (716)-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 40-50%

Ingred Name: AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000

Fraction

Ingred Name:SODIUM METABISULFITE CAS:7681-57-4 RTECS #:UX8225000 Fraction by Wt: 5-10% OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9192
=========== Hazards Identification ============
Effects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.
======================================
First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER. INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.
= Fine Fine Managemen
======================================
Flash Point:NONE Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.
========= Accidental Release Measures ==========
Spill Release Procedures:NEUTRALIZE WITH SODIUM BICARBONATE. FLUSH WITH COPIOUS AMOUNTS OF WATER. OBSERVE LOCAL, STATE & FEDERAL
REGULATIONS.
============ Handling and Storage ==============
Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED Other Precautions:NOT KNOWN
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE SHOULD BE NEEDED. Ventilation:GEN MECHANICAL RECOMMENDED. Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES Ot

by Wt: 40-50%

her Protective Equipment:FOLLOW GOOD INDUSTRIAL HYGIENE PRACTICES.
Supplemental Safety and Health
THIS IS PART A OF A 2-PART PRODUCT. SEE PNIB B FOR OTHER PART. SOLN NR
4333.

========= Physical/Chemical Properties ===============

HCC:N1

Boiling Pt:B.P. Text:>212F/>100C

Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.34

pH:5.3

Solubility in Water: COMPLETE

Appearance and Odor: CLEAR, COLORLESS, VINEGAR ODOR

Percent Volatiles by Volume:45

=========== Stability and Reactivi

ty Data ========

Stability Indicator/Materials to Avoid:YES
AVOID MINERAL ACIDS AND STRONG ALKALI
Stability Condition to Avoid:EXCESSIVE HEAT
Hazardous Decomposition Products:SULFUR DIOXIDE - AMMONIA

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATE, LANDFILL, OR FOLLOW ABOVE STEPS. OBSERVE LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulate d for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.