

BORDEN INC.,KRYLON DEPARTMENT -- KRYLON INTERIOR/EXTER ENAMEL AEROSOL 1809 --
8010-01-010-3259

=====
===== Product Identification =====

Product ID:KRYLON INTERIOR/EXTER ENAMEL AEROSOL 1809

MSDS Date:01/01/1985

FSC:8010

NIIN:01-010-3259

MSDS Number: BGDCC

=== Responsible Party ===

Company Name:BORDEN INC.,KRYLON DEPARTMENT

Address:630 E WASHINGTON

Box:390

City:NORRISTOWN

State:PA

ZIP:19404

Country:US

CA

GE:KO164

=== Contractor Identification ===

Company Name:BORDEN INC.,KRYLON DEPARTMENT

Address:630 E WASHINGTON

Box:390

City:NORRISTOWN

State:PA

ZIP:19404

Country:US

CAGE:KO164

Company Name:KRYLON PRODUCTS

Address:31500 SOLON ROAD

Box:City:SOLON

State:OH

ZIP:44139

Country:US

Phone:800-832-2541/216-566-2917

CAGE:87187

=====
===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 25%

OSHA PEL:1000PPM

ACGIH TLV:75

0PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 15%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 10%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 5%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM;
9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)
CAS:111-15-9
RTECS #:KK8225000
Fraction by Wt: 3%
OSHA PEL:S,100 PPM
ACGIH TLV:S, 5 PPM; 9192

=====
Hazards Identification
=====

Effects of Overexposure:DIZZY,CONFUSION,WEAKNESS.

=====
First Aid Measures
=====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF SPRAYED IN EYES,WASH WITH
WATER 15 MINUTES,SEE A PHYSI

CIAN.

===== Fire Fighting Measures =====

Extinguishing Media:CO,CO2,FOAM,DRY CHEMICAL

Fire Fighting Procedures:WATER FOG TO COOL CANS TO PREVENT EXPOSURE TO HIGH TEMPS

Unusual Fire/Explosion Hazard:FLAME FRONT IF SPRAYED DIRECTLY AT A OPEN FLAME.CANS MAY BURST WITH VIOLENCE WHEN EXPOSED TO HEAT

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION SOAK UP WITH ABSORBENT MATERIAL.VE NTILATE AREA.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURE OVER 120F.AVOID RADIATORS,STOVES,DIRECT SUNLIGHT OR OTHER HEAT SOURCES.HIGH TEMP MAY CAUSE BURSTING.

Other Precautions:AVOID PUNCTURING.IF SPRAY IS BURNED DO NOT BREATH IRRITATING OR TOXIC FUMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED WITH ADEQUAT VENTILATION

Ventilation:SUPP

LEMENT NATURAL VENTILATION AS NEEDED

Eye Protection:DESIRABLE

Supplemental Safety and Health

ADD HAZ ING:PIGMENTS 0.4-8%,CELLULOSE NITRATE,ALCOHOL-ALKYD,DIOCTYL PHTHALATE 16%,BUTANOL 3%,METHYLENE CHLORIDE 10%,METHYL ETHYL KETONE 5%.PERCENTAGES OF INGREDIENTS ARE APPROXIMATE

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>1

Spec Gravity:1

Solubility in Water:SLIGHT

Percent Volatiles by Volume:80

===== Stability and Reactivity Data

=====

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: BURNING SPRAY MAY PRODUCE TOXIC AND IRRITATING COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods: AVOID INCINERATION OF CAN OR USE ONLY A STRONG CLOSED INCINERATOR. DRIED ENAMEL DISCARD AS NON-DANGEROUS TRASH TO BE BURIED OR BURNED IN ACCORDANCE WITH STATE, FEDERAL AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.