View NSN Online: https://aerobasegroup.tw/nsn/6850-01-015-0834

AMERICAN OVERSEAS INDUSTRIES, DIST - SEYMOUR, MFR -- BLUE TOOL MAKERS INK 16358 -- 6850-01-015-0834

============= Product Identification =================

Product ID:BLUE TOOL MAKERS INK 16358

MSDS Date:01/01/1985

FSC:6850

NIIN:01-015-0834

MSDS Number: BGDLX === Responsible Party ===

Company Name: AMERICAN OVERSEAS INDUSTRIES, DIST - SEYMOUR, MFR

Address:RICHMOND INTERNATIONAL AIRPORT

Box:H

City:RICHMOND

State:VA ZIP: 23150

Country:US CAGE:9S525

=== Contractor Identification ===

Company Name: AMERICAN OVERSEAS INDUSTRIES CORP

Address: RICHMOND INTERNATIONAL AIRPORT

Box:H

City:RICHMOND

State:VA ZIP:23150 Country:US CAGE:9S525

======= Composition/Information on Ingredients ========

Ingred Name: ISOPROPYL ACETATE

CAS:108-21-4

RTECS #:AI4930000 Fraction by Wt: 14.4%

OSHA PEL:250 PPM/310 STEL ACGIH TLV:250 PPM/310STEL;9192

Ingred Name: ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000 Fraction by Wt: 3

9.6%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 3.74%

OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000 Fraction by Wt: 11.0% OSHA PEL:1000 PPM

ACGIH TLV:ASPHYXIANT; 9192

Ingred Name: ISOBUTANE

CAS:75-28-5

RTECS #:TZ4300000 Fraction by Wt: 11.0%

======= Hazards Ide

Effects of Overexposure: ANESTHETIC IRRIT OF RESP TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION, HDACHE, COMA.

First Aid:FUMES: REMOVE FROM EXPOSURE, RESTORE BRTHNG. KEEP WARM/QUIET. NOTIFY DOCTOR. EYES: FLUSH W/COPIOUS QTY RUNNING WATER FOR AT LEAST 15 MIN. TAKE TO MD FOR MED TREATMENT. SKIN: REMOVE W/SOAP & WATER, REM OVE CONTAM CLOTHING.

======= Fire Fighting Me

Flash Point:-10F Lower Limits:1.10 Upper Limits:2.55 Extinguishing Media:CO*2, DRY CHEM, FOAM Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. USE H*2O TO COOL CNTNRS. Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY BE CAUSE OF BURSTING AEROSOL CAN
========== Accidental Release Measures ============
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, AVOID BRTHNG VAPORS, VENT AREA.
======================================
torage ====================================
Handling and Storage Precautions:DO NOT STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:AVOID CONTINUOUS BRTHNG OF VAPORS & SPRAY MIST Ventilation:USE W/ADEQUATE VENT Protective Gloves:RUBBER Eye Protection:SAFETY GOGGLES Supplemental Safety and Health FSCM 9S525 FOR DISTRIBUTOR AMERICAN OVERSEAS INDUSTRIES CORP, SINCE MFR SEYMOU R OF SYCAMORE, INC FSCM NOT AVAILABLE DUE TO THEM NOT HAVING ONE ASSIGNED.
=========== Physical/Chemical Properties =============
HCC:V3 Appearance and Odor:LIQUID, ODOR OF ALCOHOL & ACETONE Percent Volatiles by Volume:85.0
======================================
Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:MAY PRODUCE HAZ FUMES WHEN HEATED TO DECOMP, CO
======== Disposal Considerations =======

asures ==========

========

Waste Disposal Methods:DO NOT INCINERATE AEROSOL, DISPOSE OF IAW LOCAL, STATE, FED REG.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.