View NSN Online: https://aerobasegroup.tw/nsn/6810-01-016-5196

ALLIED CHEMICAL CORP. -- NITRIC AIC, RED FUMING -- 6810-01-016-5196

Product ID:NITRIC AIC, RED FUMING MSDS Date:01/01/1985 FSC:6810 NIIN:01-016-5196 MSDS Number: BGDQW === Responsible Party === Company Name: ALLIED CHEMICAL CORP. Address:COLUMBIA RD & PARK AVE Box:1087R City:MORRISTOWN State:NJ ZIP:07960 Country:US CAGE:1L168 === Contractor Identification === Compan y Name: ALLIED CHEMICAL COMPANY Box:1087R CAGE:1L168 Company Name: ALLIED-SIGNAL INC Address:Box:2332R City:MORRISTOWN State:NJ ZIP:07962-2332 Country:US Phone:201-455-4414 CAGE:1L164

Ingred Name:NITRIC ACID (SARA III) CAS:7697-37-2 RTECS #:QU5775000 Fraction by Wt: >90% OSHA PEL:2 PPM/4 STEL ACGIH TLV:2 PPM/4 STEL; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Effects of Overexposure:SEVER BURNS TO EYES, SKIN, INHAL OF VAPOR DAMAGES RESPIR TRACT. SYMPTOMS MAY BE DELAYED.

First Aid:SKIN:FLUSH W WATER.EYES:FLUSH W/WATER 15 MIN.GET IMMED MEDICAL ATTN.IF INHALED:REMOVE TO FRESH AIR,GET IMMEDIATE MEDICAL ATTENTION.

Extinguishing Media:IF INVOLVED IN A FIRE,USE WATER SPRAY. Fire Fighting Procedures:AV OID INHAL OF GAS.USE SELF-CNTND BRTHG APP. Unusual Fire/Explosion Hazard:WILL INCREAS FLAMABILITY OF WOOD,ORGANICS.CAUSES EXPLOS W H\*25,METAL POWDERS,CARBIDES,TURPENTINE.

Spill Release Procedures: FLUSH WITH PLENTY OF WATER AND NEUTRALIZE WITH ALKALINE MATL SUCH AS SODA ASH, LIME, ETC. PROVIDE ADEQUATE VENTILATION AS OXIDES OF NITROGEN AND CO\*2 ARE GENERATED DURING NEUTRALIZATION.

======= Handl

Handling and Storage Precautions:STORE IN WELL VENTILATED PROPERLY DRAINED SITE AWAY FROM HEAT,SUN.ISOLATE FROM METALS,ORGANICS,WOOD,PAPER PRODUCTS.
Other Precautions:NITRIC ACID VAPRO AND OXIDES ARE INSIDIOUS.SUMPTOMS FROM INHALATION MAY BE DELAYED.DO NOT BREATH FUMES.SEE MCA CHEMICAL SAFETY DATA SHEET SD-5,FROM MANUFACT CHEM ASSO. IN WASHINGTON D.C.

======= Exposure Controls/Personal Protection ===============

**Respiratory Protect** 

ion:USE SELF-CNTND OR CLEAN AIR SUPPLIED BREATHING APPARATUS
Ventilation:LOCAL EXHAUST SUFFICIENT TO ELIMINATE ALL FUMES
Protective Gloves:NEOPRENE
Eye Protection:CHEM SAFETY GOGGLES
Other Protective Equipment:NEOPREN APRON/SHOES,HARD HAT,NEOPRENE CLOTHNG,FACE SHIELD
Supplemental Safety and Health BP:471-484C.

## HCC:D2

Boiling Pt:B.P. Text:244-251F Vapor Pres:3.0 Vapor Density:3.2 Spec Gravity:1.41 Evaporation Rate & amp ; Reference:ESSENTIALLY 1 Solubility in Water:COMPLETE Appearance and Odor:COLORLESS TO LIGHT YELLOW WITH ACRID ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES METALS,H\*2S,WOOD,EXCELSIOR,PAPER PRODUCTS,SIMILAR ORGANICS. Hazardous Decomposition Products:POISONOUS OXIDES OF NITROGEN(GASEOUS)

Waste Disposal Methods:DILUTE AND NE UTRALIZE.IF PERMITTED BY LOCAL,STATE AND FEDERAL REGULATIONS,FLUSH NEUTRAL RESIDUE TO SEWER WITH PLENTY OF WATER.CONTACT LOCAL AUTHORITIES FOR DISPOSAL COMPLIANCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any pe

rson utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.