

HOFFER'S,INC. PAINT DIV. -- TRAFFIC PAINT -- 8010-01-018-2722

=====
Product Identification
=====

Product ID:TRAFFIC PAINT

MSDS Date:01/01/1985

FSC:8010

NIIN:01-018-2722

MSDS Number: BGDVJ

=== Responsible Party ===

Company Name:HOFFER'S,INC. PAINT DIV.

Emergency Phone Num:715-845-7221

CAGE:MO562

=== Contractor Identification ===

Company Name:HOFFER'S,INC. PAINT DIV.

CAGE:MO562

Company Name:HOFFERS

INC PAINT DIV

Address:310 BELLIS ST

Box:777

City:WAUSAU

State:WI

ZIP:54401-6333

Country:US

Phone:715-845-7221

CAGE:60020

=====
Composition/Information on Ingredients
=====

Ingred Name:PIGMENTS

Fraction by Wt: 40.3%

Ingred Name:VEHICLE

Fraction by Wt: 31.9%

Ingred Name:ADDITIVES

Ingred Name:AMMONIA (SARA III)

CAS:7664-41-7

RTECS #:BO0875000

Fraction by Wt: 0.2%

OSHA PEL:50 PPM

ACGIH TLV:25 PPM/35 STEL; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:RESIDUAL MON

OMERS

Fraction by Wt: 0.15%

ACGIH TLV:10PPM

===== Hazards Identification =====

Effects of Overexposure:AMMONIA,FORMALDEHYDE,ANDRESIDUAL MONOMER VAPORS
MAY BE IRRITATING TO EYES,SKIN,MUCOUS MEMBRANES,RESP

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR IMMEDIATELY;FLUSH EYES WITH PLENTY OF
WATER FOR AT LEAST 15 MINUTES AND CONSULT PHYSICIAN;WASH SKIN
THOROUGHLY:WITH SOAP AND WATER.

===== Fire Fighting Measures =====

Extinguishing Media:NON-FLAMMABLE
Fire Fighting Procedures:NON-FLAMMABLE

===== Accidental Release Measures =====

Spill Release Procedures:DIKE AND CONTAIN SPILL WITH INERT MATERIAL
(DRY SAND,EARTH,ETC.)AND TRANSFER THE LIQUID TO CONTAINERS FOR
RECOVERY OR DISPOSAL.FLOORS MAY BE SLIPPERY CARE SHOULD BE EXECISED
TO AVOID FALLS.

===== Handling and Storage =====

Hand
ling and Storage Precautions:KEEP FROM FREEZING-PRODUCT STABILITY
MAY BE AFFECTED.

Other Precautions:RESIDUAL MONOMER CONTENT UNDER CONDITIONS OF NORMAL
HANDLING PRESENT NO PROBLEM;HOWEVER,HIGH LEVELS OF MONOMER VAPOR
CAN BE RELEASED INTO WORKROOM ATMOSPHERE WHEN EMULSIONS ARE HEAT
CURE OR D

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR MESA/NIOSH APPROVED RESPIRATOR
Ventilation:LOCAL EXHAUST AND MECHANICAL
Protective Gloves:IMP

ERVIOUS GLOV

Eye Protection:ANSI Z87.1,1968 SPLASHPRO

Other Protective Equipment:EYEWASH STATION, EMERGENCY SHOWER.

Supplemental Safety and Health

FORMALDEHYDE LP89250000, 0.03%;TLV 2PPM; LEAD CHROMATE OF9626000,

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F 100 C

Vapor Pres:1/M

Vapor Density:WATE

Spec Gravity:1.0-1

Evaporation Rate & Reference:BUTYL ACETATE

Solubility in Water:DILUTABLE

Appearance and Odor:YELLOW LIQUID-AMMONIACAL OD

OR

Percent Volatiles by Volume:0.36

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD:OXIDES
OF CARBON,TOXIC MONOM

===== Disposal Considerations =====

Waste Disposal Methods:KEEP SPILLS OUT OF MUNICIPAL SEWERS AND OPEN
BODIES OF WATER THE MATERIAL SHOULD BE INCINERATED IN APPROVED
EQUIPMENT.DIKING MATERIAL SHOULD BE LAND FIL

LED ACCORDING TO

CURRENT LOCAL,STATE AND FEDERAL REGULATIONS.CLEAR WATER MAY BE
SEWEREDFOR BIOLOG

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advi

ce to verify and
assume responsibility for the suitability of this information to their
particular situation.