

CAULK/DENTSPLY -- REPAIR LIQUID -- 6520-01-020-1426

===== Product Identification =====

Product ID:REPAIR LIQUID

MSDS Date:01/01/1987

FSC:6520

NIIN:01-020-1426

MSDS Number: BGDYL

=== Responsible Party ===

Company Name:CAULK/DENTSPLY

Address:LAKEVIEW AND CLARKE AVE

Box:359

City:MILFORD

State:DE

ZIP:19963

Country:US

Info Phone Num:302-422-4511

Emergency Phone Num:302-422-4511

CAGE:11107

=== Contracto

r Identification ===

Company Name:CAULK/DENTSPLY

Address:38 W CLARKE AVE

Box:359

City:MILFORD

State:DE

ZIP:19963-0359

Country:US

Phone:302-422-4511/ 703-451-1900

CAGE:11107

===== Composition/Information on Ingredients =====

Ingred Name:METHYL METHACRYLATE (SARA III)

CAS:80-62-6

RTECS #:OZ5075000

Fraction by Wt: 92.5%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYLENE GLYCOL DIMETHACRYLATE

CAS:97-90-5

RTECS #:KW5500000

Fra

ction by Wt: 7.5%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,AND
RESPIRATORY TRACT;HEADACHE,NAUSEA,POSSIBLE CORNEAL DAMAGE.
CHRONIC:RESPIRATORY PROBLEM AND POSSIBLE EYES DAMAGE.
Effects of Overexposure:SEE HEALTH HAZARDS DATA.
Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
First Aid Measures
=====

First Aid:SKIN AND EYES:FLUSH WITH PLENTY OF WATER FOR ABOUT 15
MINUTES;CALL A PHYSICIAN. INHALATION:REMOVE TO FRESH AIR.CALL A
PHYSICIAN IF NEEDED. INGESTION:IF CONSCIOUS,INDUCE VOMITING AND
CONSULT A PHYSICIA N IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:OC
Flash Point:50F/10C
Lower Limits:2.1
Upper Limits:12.5
Extinguishing Media:FOAM,CO*2,DRY CHEMICAL.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN E
NCLOSED
AREA.
Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY RUPTURE CONTAINERS
WITH EXPLOSION.

=====
Accidental Release Measures
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE
LIQUID IF POSSIBLE;USE INERT ABSORBENT MATERIAL AND COLLECT FOR
PROPER DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY AREA;USE WITH AN
ADEQUATE VENTILATION;KEE

P AWAY FROM HEAT,OPEN FLAMES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS AND MIST OR SCBA IN AN ENCLOSED AREA IF ABOVE PEL/TLV.

Ventilation:LOCAL EXHAUST (EXPLOSION PROOF).

Protective Gloves:IMPERVIOUS.

Eye Protection:SPLASH PROOF GOGGLES.

Other Protective Equipment:APRON,IMPERVIOUS BOOTS,EYE-WASH/SAFETY SHOWER.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE

VAPORS/MIST.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=101.1C, 214.F

Vapor Pres:29

Vapor Density:3.45

Spec Gravity:0.94

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS LIQUID.

Percent Volatiles by Volume:92.5

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZER.

Stability Condition to Avoid:EXTREME HEAT & IGNITION SOURCES.

Hazardous

Decomposition Products:ACRID FUMES & CO AND/OR CO*2.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to

be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.