View NSN Online: https://aerobasegroup.tw/nsn/6630-01-022-7406

Product ID:AK-1 ACID TEST KIT, PART B: INDICATOR MSDS Date:05/28/1991 FSC:6630 NIIN:01-022-7406 Kit Part:Y **MSDS Number: BGFDG** === Responsible Party === Company Name: SPORLAN VALVE COMPANY Address:7525 SUSSEX AVE. City:ST LOUIS State:MO ZIP:63143 Info Phone Num:314-647-2775 Emergency Phone Num:314-647-2775 CAGE:78462 === Contractor Identification === Company Name: SPORLAN VALVE COMPANY Address:7525 SUSSEX AVE. Box:City:ST LOUIS State:MO ZIP:63143 Phone:314-647-2775 CAGE:78462

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 62% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LB S

Ingred Name: ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 36% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9293

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 2% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: PHENOL RED CAS:143-74-8 RTECS #:SJ7490000 Fraction by Wt: TRACE Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: CAUSES EYE AND SKIN IRRITATION. INGESTION AND INHALATION MAY CAUSE DROWZINESS/UNCONSCIOUSNESS. Effects of Overexposure: IRRITATION, DROWSINESS, HEADACHE AND DIZZINESS OR UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure: LIVER AND SKIN.

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED. EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN CONTACT: WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS PERSIS T. INGESTION: DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF WATER. GET MEDICAL HELP IMMEDIATELY.

Flash Point Method:TCC Flash Point:60F/15.6C Lower Limits:2 Extinguishing Media:CO2,DRY CHEM ICAL OR FOAM. Fire Fighting Procedures:NONE STATED. Unusual Fire/Explosion Hazard:NONE STATED.

	Accidental	Release	Measures	
--	------------	---------	----------	--

Spill Release Procedures:SMALL AMOUNTS MAY BE FLUSHED AWAY WITH WATER OR COLLECTED FOR INCINERATION.

Handling and Storage Precautions:DO NOT STORE SOLUTIONS ABOVE 120F. Other Precautions:KEEP HEAT AND IGNITION SOURCES AWAY.

Respiratory Protection:USUALLY NONE. Ventilation:NORMAL VENTILATION. Protective Gloves:RUBBER Eye Protection:CHEMICAL GOGGLES. Other Protective Equipment:APRON Work Hygienic Practices:DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH THIS PRODUCT. Supplemental Safety and Health

HCC:F2 Boiling Pt:=83.3C, 182.F Melt/Freeze Pt:1 Spec Gravity:0.88 pH:7 Solubility in Water:SLIGHT Appearance and Odo r:YELLOW-ORANGE-RED LIQUID Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES NONE STATED Stability Condition to Avoid:NONE STAT4D Hazardous Decomposition Products:OXIDES OF CARBON.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compili

ng agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.