View NSN Online: https://aerobasegroup.tw/nsn/5805-01-024-1052

Product ID:GELLA 4441 REENT. ENCAP. CMPD-B/BB3-24 GEL MSDS Date:01/01/1987 FSC:5805 NIIN:01-024-1052 Kit Part:Y MSDS Number: BGFJZ === Responsible Party === Company Name:3M CO. TELCOMM PRDS. DVI. Emergency Phone Num:612-733-1110 CAGE:55203 === Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO TELCOMM MARKETS DIV Address:3M AUSTIN CTR Box:City:AUSTIN State:TX ZIP:79769-2963 Country:US Phone:800-426-8688 CAGE:55203

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE (BOILING RANGE 710-865F); RANGE 30-40% Fraction by Wt: 35%. ACGIH TLV:5 MG/CUM

Ingred Name:ANTIOXIDANT, TYPE NOT SPECIFIED; RANGE 0.1-1% Fraction by Wt: 0.55%

Ingred Name:HYDROCARBON POLYOL; RANGE 60-70% Fraction by Wt: 65%.

Ingred Name:ORGANIC TIN COMPOUND Fraction by Wt: 0.3% OSHA PEL:S, 0.1 MG/M3 (SN) ACGIH TLV:S, 0.1 MG/M3 (SN)

Effects of Overexposure:EYE:MAY IRRITATE; SKIN:MAY CAUSE MILD IRRITAT; INHAL: HAZARD CONSIDERED LOW; INGEST:SLIGHT IRRITAT.

First Aid:EYES:IMMED. FLUSH W/WATER FOR >10 MIN.-GET MED. ATTN.; SKIN:REMOVE CONTAMIN. CLOTHNG & WASH AFFE CTED AREA THOROUGHLY W/SOAP & WATER; INHAL:PROVIDE FRESH AIR-IF BREATHNG DIFFICULTIES,DISCONTINUE EXPOSU RE-GET MED.ATTN.; INGEST:DONOT INDUCE VOMIT-GET DR

Flash Point:>270F/>132C TCC Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL Fire Fighting Procedures:MFR STATES: "NONE" Unusual Fire/Explosion Hazard:AVOID SOURCES OF IGNITION, INCLUDING STATIC SPARK

======== Accidental Release Measures

\_\_\_\_\_

Spill Release Procedures: PART B: POUR INERT ABSORBENT OVER SPILL. COLLECT INTO A DRUM.

Handling and Storage Precautions: AVOID EYE & SKIN CONTACT. SAFETY GLASSES/GOGGLES & IMPERVIOUS GLOVES. AVOID PROLONGED/REPEATED BREATHING OF VAPORS. USE ONLY IN WELL VENTILATED AREAS.
Other Precautions: KEEP AWAY FROM IGNITION SOURCES, INCLUDING STATIC SPARKS. KEEP OUT OF CHILDREN'S REACH. LAUNDER CONTAMINAT
ED CLOTHING BEFORE REUSE.

Respiratory Protection:NIOSH MSHA APPRVD ORGANIC VAPOR/MIST RESPIRATOR IF NEEDED/TLV EXCEED Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION Protective Gloves:IMPERVIOUS Eye Protection:SAFETY/CHEM GOGGLES Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT. Supplemental Safety and Health MSDS DATED:11/13/85;P/N CITED IS FOUND IN KIT PROCURED UNDER P/ "BB3-24/GEL" FOR THIS NSN.KEY1:N1.

HCC:N1 Spec Gravity:0.90 Viscosity:3000 CPS Solubility in Water:INSOLUBLE Appearance and Odor:CLEAR, OILY LIQUID Percent Volatiles by Volume:NIL

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HIGH TEMPERATURES,IGNITION SOURCES Hazardous Decomposition Products:THERMAL DECOMPOS./BURNING MAY PRODUCE: CO, CO\*2, HCN Conditions to Avoid Polymerization:MFR. CITES NONE

Waste Disposal Methods: PARTS A/B MAY BE BURIED IN A CONTROLLED LANDFILL OR INCINERATED IAW STATE & LOCAL REGULATIONS. CURED MATER. MAY BE BURIED IN A SANITARY LANDFILL IAW STATE & LOCAL REGS. PARTS A/B ARE NOT HAZARDOUS WAS TES UNDER EPA RCRA STDS (40 CFR 261).

Disclaimer (provided with this information by the comp iling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

Ν