View NSN Online: https://aerobasegroup.tw/nsn/6140-01-024-8980

LIGHTALARMS ELECTRONICS CORP (GRAYBAR DISTR-1B241) -- L-3 (SEE ADDTL DATA) -- 6140-01-024-8980

Product ID:L-3 (SEE ADDTL DATA)

MSDS Date:01/01/1985

FSC:6140

NIIN:01-024-8980

MSDS Number: BGFLX === Responsible Party ===

Company Name: LIGHTALARMS ELECTRONICS CORP (GRAYBAR DISTR-1B241)

Address:1510 TOMLYNN ST

City:RICHMOND

State:VA

ZIP:23230-3313

Country:US

CAGE:0272

0

=== Contractor Identification ===

Company Name: GRAYBAR ELECTRIC CO INC

Address:1510 TOMLYNN ST

Box:City:RICHMOND

State:VA

ZIP:23230-3313

Country:US

Phone:804-359-1381

CAGE:1B241

Company Name: LIGHTALARMS ELECTRONICS CORP

Address:1170 ATLANTIC AVENUE

Box:City:BALDWIN

State:NY

ZIP:11510-4205 Country:US

Phone:516-379-1000

CAGE:02720

======= Composition/Information on Ingredients ========

Ingred Name: SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000 Fraction by Wt: 31%

OSHA P

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 69% =========== Hazards Identification ========================== Effects of Overexposure:H*2504 IS CORROSIVE. IT WILL CAUSE FIRST DEGREE SKIN BURNS. First Aid:FLOOD WITH FRESH WATER.SEEK MEDICAL ASSISTANCE. Flash Point:NONE Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard: BATTERY MAY OUTGAS HYDROGEN GAS AT ELEVATED TEMPERATURE OR DURING OVERCHARGE Spill Release Procedures:FLOOD WITH WATER TO DILUTE - COVER WITH SODIUM CARBONATE OR AN EQUAL MIXTURE OF SODA ASH & SLAKED LIME. AFTER MIXING, ADD WATER IF NECESSARY TO FORM A SLURRY. ============ Handling and Storage =========================== Han dling and Storage Precautions: WEAR RUBBER GLOVES, GOGGLES AND APPROPRIATE PROTECTIVE CLOTHING WHEN HANDLING WET BATTERIES. ====== Exposure Controls/Personal Protection ======== Ventilation: ADEQUATE Protective Gloves: RUBBER Eye Protection: GOGGLES OR SAFETY GLASSES Supplemental Safety and Health ========== Physical/Chemical Properties ===================== HCC:C1 Spec Gravity:1.220 Solubility in Water: COMPLETE Appearance and Odor: CLEAR - SULFUROUS ODOR ===========

EL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:HYDROGEN GENERATED, WHEN ITEM
CONNECTED TO BATTERY CHARGER.

== Stability and Reactivity Data =========

======= Disposal Considerations ============

Waste Disposal Methods:ADD SLOWLY TO A LARGE AMT OF SOLUTION OF SODA ASH & SLAKED LIME BY STIRRING. DISCHARGE SOLUTION WITH LARGE AMT OF WATER INTO A LINED SINK OF PROTECTIVE MATTING, & FILLED WITH CHIPPED MARBLE.

Disclaim

er (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.