

POWER CONVERSION INC -- BA-5598/U LITHIUM BATTERY -- 6135-01-034-2239

=====
Product Identification
=====

Product ID:BA-5598/U LITHIUM BATTERY

MSDS Date:01/01/1987

FSC:6135

NIIN:01-034-2239

MSDS Number: BGGHC

=== Responsible Party ===

Company Name:POWER CONVERSION INC

Address:495 BOULEVARD

City:ELMWOOD PARK

State:NJ

ZIP:07407-2029

Country:US

Info Phone Num:201-796-4800

Emergency Phone Num:201-796-

4800

CAGE:5G978

=== Contractor Identification ===

Company Name:HAWKER ETERNACELL, INC.

Address:495 BOULEVARD

Box:City:ELMWOOD PARK

State:NJ

ZIP:07407-2029

Country:US

Phone:201-796-4800 /FAX: 201-796-6243

CAGE:5G978

=====
Composition/Information on Ingredients
=====

Ingred Name:SULFUR DIOXIDE (SARA III)

CAS:7446-09-5

RTECS #:WS4550000

Fraction by Wt: 30%

OSHA PEL:5 PPM/5 STEL

ACGIH TLV:2 PPM/5 STEL; 9293

Ingred Name:ACETONITRILE (SARA III)

CAS:75-05-8

RTECS #:AL7700000

Frac

tion by Wt: 10%
OSHA PEL:40PPM/60 STEL
ACGIH TLV:40PPM/60STEL; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:LITHIUM
CAS:7439-93-2
RTECS #:OJ5540000
Fraction by Wt: 4%
ACGIH TLV:NONE

=====
===== Hazards Identification =====

Effects of Overexposure:SEVERE EYE AND RESPIRATORY TRACT IRRITATION,
PULMONARY EDEMA RESULTS FROM ACUTE EXPOSURE

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH COPIOUS AMOUNTS OF WATER, SEEK
MEDICAL ATTENTION, SKIN CONTACT: FLUSH WITH WATER AND REMOVE
CLOTHING, INHALATION: MOVE TO FRESH AIR, BEGIN CPR IF BREATHING HAS
STOPPED,SEEK MEDICAL ATTENTION

=====
===== Fire Fighting Measures =====

Extinguishing Media:SAND, METAL-X, DRY CHEMICAL, DO NOT USE CO₂
EXTINGUISHER
Fire Fighting Procedures:USE CLASS D EXTINGUISHER FOR LITHIUM FIRE
Unusual Fire/Explosion Hazard:CELLS VENT SO₂ AND ACETONITRILE IF
HEATED ABOVE 160
F, TEMPERATURES ABOVE 345 F MELT LITHIUM

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA IF CELL VENTS OR IS RUPTURED,
CLEAR ALL PERSONNEL FROM THE AREA FLUSH AWAY LIQUID ELECTROLYTE
WITH WATER, USE APPROPRIATE EYE/SKIN PROTECTION. RESPIRATORY
PROTECTION MAY BE NECESSARY IN AREAS WITH INADEQUATE VENTILATION.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE BATTERIES

RIES IN COOL, DRY, AREA
WITH ADEQUATE VENTILATION. SEGREGATE FROM FLAMMABLE/COMBUSTIBLE
LIQUIDS. PROVIDE SPRINKLER SYSTEMS
Other Precautions:DO NOT HEAT, CRUSH, OR DISASSEMBLE THESE BATTERIES.
DO NOT SHORT-CIRCUIT OR BYPASS THE INTERNAL FUSES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE FULL-FACE PRESSURE DEMAND SCBA FOR CONFINED
SPACE OR FIRES
Ventilation:ADEQUATE TO MAINTAIN SO*2 LEVELS BELOW TLV IN STORAGE AREA
Protective Gl
oves:RUBBER/NEOPRENE
Eye Protection:CHEMICAL GOGGLES
Supplemental Safety and Health
MSDS DATED OCT.31,1985

===== Physical/Chemical Properties =====

HCC:Z6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
LITHIUM REACTS WITH WATER TO PRODUCE HYDROGEN GAS
Stability Condition to Avoid:TEMPERATURES ABOVE 160 F, SHORT-CIRCUITING
Hazardous Decomposition Products:SULFUR DIOXIDE, HYDROGEN CYANIDE,
LITHIUM O
XIDES

===== Disposal Considerations =====

Waste Disposal Methods:LAND DISPOSAL IS PROHIBITED UNLESS THE BATTERY
IS RENDERED NON-REACTIVE. RETURN ALL DEPLETED BATTERIES TO THE
LOCAL DEFENSE REUTILIZATION AND MARKETING OFFICE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied,

warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.