## 

Product ID:PD-16Z GREEN MSDS Date:01/01/1985 FSC:5970 NIIN:01-038-0590 MSDS Number: BGGWD === Responsible Party === Company Name:PDI,INC Address:3760 FLOWEFIELD RD City:BLAINE State:MN ZIP:55434 Country:US Info Phone Num:612-785-2156 Emergency Phone Num:612-785-2156 CAGE:DO976 === Contractor Identification === Company N ame:P D I INC Address:3760 FLOWEFIELD RD Box:City:CIRCLE PINES State:MN ZIP:55014 Country:US Phone:612-785-2156 CAGE:55638 Company Name: PDI, INC Address:3760 FLOWEFIELD RD Box:City:BLAINE State:MN ZIP:55434 Country:US CAGE:DO976

Ingred Name:SYNTHETIC RESIN Fraction by Wt: 23.0%

Ingred Name:PIGMENTS(VARIOUS) Fraction by Wt: 2.0%

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Frac tion by Wt: 46.0% OSHA PEL:350 PPM/450 STEL ACGIH TLV:350 PPM/450STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1

Ingred Name:METHYLENE CHLORIDE (SARA III) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 8.0% OSHA PEL:500 PPM/C,1000; Z2 ACGIH TLV:50 PPM, A2; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 19.0% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qt y:1000 LBS

Effects of Overexposure:UNCONSCIOUSNESS,COMA,ANETHESIA,HEADACHE, NAUSEA DIZZINESS ETC:MODERATE IRRITANT TO SKIN,EYES.

First Aid:IF UNCONSCIOUS OR SWALLED,CALL PHYSICIAN IMMEDIATELY.IF BREATHING STOPPED,GIVE ARTIFICIAL RESPIRATION.GIVE OXYGEN IF AVAILABLE.DO NOT INDUCE VOMITING IF UNCONSCIOUS,IF CONSCIOUS WITH SALT WATER.DO NOT U SE ADRENALINE!!

Flash Point:>200F O.C. Lower Limits:2.5 Upper Limits:9-10 Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL OR FOAM Fire Fighting Procedures:SELF CONTAINED RESPIRATORY PROTECTION WORN BY FIREMEN Unusual Fire/Explosion Hazard:VAOR FORMS EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER EXPLOSIVE LIMITS.

Spill Release Procedures:WIPE OR

MOP UP SPILLS IMMEDIATELY.RAGS OR MOPS USED FOR CLEANUP SHOULD BE PLACED IN CLOSED CONTAINERS(APPROVED)OR A SAFE PLACE OUTDOORS UNTIL DRIED.ADEQUATE PERSONAL PROTECTION PROVIDED.

Handling and Storage Precautions: KEEP AWAY FROM ARCING, OPEN FLAME AND HIGH HEAT SOURCES. PROVIDE ADEQUATE VENTILATION, AVOID LEAVING CONTAINER OPEN WHEN NOT IN USE. Other Precautions: SEAL TIGHTLY. STORE BELOW 120F.

Ventilation:LOCAL - YES Protective Gloves:NO Eye Protection:YES Other Protective Equipment:SEE SUPPLEMENTAL DATA Supplemental Safety and Health OTHER PROTECTIVE EQUIPMENT USED INCLUDE POSITIVE PRESSURE HOSE MASKS,AR LINE MASKS AND INDUSTRIAL CANISTER TYPE GAS MASKS RECOMMENDED DURING LONG PERIODS OF USE.

HCC:T6 Boiling Pt:B.P. Text:160-170 Vapor Pres:97 Vapor Density :3.9 Spec Gravity:1.12 Evaporation Rate & amp; Reference:4.5-5-BUTYL ACETAT Solubility in Water:NEGLIGIBLE Appearance and Odor:CHLOROFORM LIKE ODOR,THICK LIQUID(MAYONAISE LIKE) Percent Volatiles by Volume:69

Stability Indicator/Materials to Avoid:NO SODIUM HYDROXIDE AND ALKALI METALS,ZINC OR ALUMINUM. Hazardous Decomposition Products:HYDROGEN CHLORIDE AND OTHER TOXIC PRODUCTS(MINUTE)

====== Disposal Consider

Waste Disposal Methods:ONLY APPROVED DISPOSAL PROCEDURES OF LIQUIDS SHALL BE USED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent profess ional advice to verify and assume responsibility for the suitability of this information to their particular situation.