

PRATT AND LAMBERT,INC. -- EN ALKYD LUST RED 31136 -- 8010-01-088-0099

===== Product Identification =====

Product ID:EN ALKYD LUST RED 31136

MSDS Date:01/01/1987

FSC:8010

NIIN:01-088-0099

MSDS Number: BGLGY

=== Responsible Party ===

Company Name:PRATT AND LAMBERT,INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

CAGE:61196

=== Contractor Identification ===

Company Name

e:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:S, 50 PPM; 9394

EPA Rpt Qty:1000

LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:SILICA, AMORPHOUS, DUST
CAS:112945-52-5
RTECS #:VV7310000
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3; 8990

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTALLINE-CRISTOBALITE
CAS:14464-46-1
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:SILICA, CRYSTALLINE - FUSED
CAS:60676-86-0
RTECS #:VV7328000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

===== Hazards Identification =====

Effects of Overexposure:PNEUMOCONIOSIS,PERMANENT NERVOUS SYSTEM
DAMAGE,INTERNAL ORGAN DAMAGE.DELIBERATE INHALATION HARMFUL.

===== Firs

First Aid Measures =====

First Aid:INGESTION:INDUCE VOMITING-CONSULT PHYSICIAN.INHALATION:REMOVE TO FRESH AIR.RESTORE BREATHING.KEEP WARM AND QUIET.GET PHYSICIAN.EYES:15 MINUTE WATER FLUSH.SKIN:REMOVE CONTAMINATED CLOTHING.WASH SKIN WITH SOAP AND WATER.

===== Fire Fighting Measures =====

Flash Point:20F,-7C

Extinguishing Media:CARBON DIOXIDE,DRY CHEMICALS,ALCOHOL,POLYMER FOAMS.

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS.WATER-FOG TO

COOL CONTAINERS.

Unusual Fire/Explosion Hazard:CONTAINER EXPLOSION HAZARD DUE TO EXTREME HEAT,EXPOSURE TO SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.CONTAIN WITH INERT MATERIAL.TRANSFER TO COVERED METAL CONTAINERS.PREVENT ENTRY TO DRAINS,SEWERS AND GROUND WATER,WEAR RESPIRATORS,EYE,SKIN PROTECTION.REMOVE LIQUID WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

==

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN ACCORDANCE WITH OSHA 29CFR1910-106.KEEP CONTAINER CLOSED.DO NOT BREATHE DUST,FUMES.

Other Precautions:GROUND AND BOND CONTAINER TO RECEIVING VESSEL.DO NOT PUNCTURE,CUT OR WELD EMPTY CONTAINER.DO NOT WASH AND RE-USE CONTAINERS.DO NOT USE PRESSURE TO EMPTY CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory

Protection:NIOSH/OSHA RESPIRATOR IN ACCORDANCE WITH 29 CFR 1910.134

Ventilation:LOCAL EXHAUST TO REMOVE FLAMMABLE DECOMPOSITION PRODUCTS.

Protective Gloves:SOLVENT RESISTANT

Eye Protection:SHIELDED SAFETY GLASSES.

Other Protective Equipment:EYEWASH FACILITY,SAFETY SHOWER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:190F,88C

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatile

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG ACIDS, ALKALINES, OXIDIZERS.
Stability Condition to Avoid: EXCESSIVE HEAT. SOURCES OF IGNITION.
Hazardous Decomposition Products: CO, CO*2, SMOKE FROM IGNITION

===== Disposal Considerations =====

Waste Disposal Methods: DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE OF
IN ACCORDANCE WITH EPA, LOCAL, STATE AND FEDERAL REGULATIONS FOR
FLAMMABLE, HAZOUDOUS WASTES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this informat
ion to their
particular situation.