View NSN Online: https://aerobasegroup.tw/nsn/6850-01-205-0296

RICOH CORPORATION -- 4085 TONER #887132 -- 6850-01-205-0296

=========== Product Identification ==============

Product ID:4085 TONER #887132

MSDS Date:08/18/1989

FSC:6850

NIIN:01-205-0296

MSDS Number: BGQNP === Responsible Party ===

Company Name: RICOH CORPORATION

Address:5 DEDRICK PLACE

City:WEST CALDWELL

State:NJ ZIP:07006 Country:US

Info Phone Num:201-882-2000

Emergency Phone Num:800-336-6737

Preparer's Name:KR

ISTINA SAGE CAGE:54726

=== Contractor Identification ===

Company Name: RICOH CORPORATION

Address:5 DEDRICK PLACE

City:WEST CALDWELL

State:NJ

ZIP:07006-6304

Country:US

Phone:800-336-6737

CAGE:54726

======= Composition/Information on Ingredients ========

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000 Fraction by Wt: 13% OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:STYRENE ACRYLIC RESIN

Fraction by Wt: 85%

Ingred Name: VICTORIA BLUE B BASE DYE

CAS:2390-60-5

Frac

tion by Wt: 2%
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: MAY CAUSE TEMPERARY EYE DISCOMFORT. MAY CAUSE SLIGHT IRRITATION ON PROLONGED AND REPEATED CONTACT WITH THE SKIN. INHALATION: GASPING. THERE ARE NO CHRONIC LONG TERM EFFECTS.
Effects of Overexposure:MINIMAL RESPIRATORY TRACT IRRITATION MAY OCCUR AS
WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:INHALE- REMOVE FROM EXPOSURE TO FRESH AIR. EYE- OPEN EYE AND FLUSH WITH PLENTY OF WATER. SKIN- WASH WITH SOAP AND WATER. INGEST-DRINK SEVERAL GLASSES OF WATER. CALL A PHYSICIAN.
======================================
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.
Fire Fighting Procedures:NO SPECIAL FIRE FIGHTING PROCEDURE NECESSARY Unusual Fire/Explosion Hazard:WILL NOT OCCUR
========= Accidental Release Measures ==========
Spill Release Procedures:SWEEP MATERIAL ONTO PAPER AND PLACE IN FIBER CARTON; VACUUM USING APPROVED TONER VACUUM CLEANER WITH A .5 MICRON FILTER. Neutralizing Agent:NONE
======================================
Handling and Storage Precaut ions:KEEP OUT OF REACH OF CHILDREN. CLEANSE SKIN THOROUGHLY AFTER CONTACT, BEFORE BREAKS AND MEALS, AND AT THE END OF WORK PERIODS. Other Precautions:NONE
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE SPECIFIED BY MANUFACTURER. Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT. Protective Gloves:NONE NORMALLY REQUIRED

Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIE Protective Gloves:NONE NORMALLY REQUIRED Eye Protection:NONE NORMALLY REQUIRED Other Protective Equipment:NONE Work Hygienic Practices:WASH HANDS AFTER C

ONTACTING MATERIAL.
Supplemental Safety and Health
MSDS DATE:9/5/86

======== Physical/Chemical Properties =========

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:176F,80C

Spec Gravity:0.34 Solubility in Water: