

TICONIUM CO;DIV OF CMP INDUSTRIES INC. -- TI-SEAL (ETHYL ACETATE) -- 6810-00-245-6695
===== Product Identification =====

Product ID:TI-SEAL (ETHYL ACETATE)
MSDS Date:01/01/1987
FSC:6810
NIIN:00-245-6695
MSDS Number: BGTJY
=== Responsible Party ===
Company Name:TICONIUM CO;DIV OF CMP INDUSTRIES INC.
Address:413-N PEARL
City:ALBANY
State:NY
ZIP:12201
Country:US
Info Phone Num:518-434-3147
Emergency
Phone Num:518-434-3147
CAGE:KO822
=== Contractor Identification ===
Company Name:TICONIUM CO DIVISION OF CMP INDUSTRIES INC
Address:413 N PEARL ST
Box:City:ALBANY
State:NY
ZIP:12207-1311
Country:US
Phone:518-434-3147
CAGE:65024
Company Name:TICONIUM CO;DIV OF CMP INDUSTRIES INC.
Address:413-N PEARL
City:ALBANY
State:NY
ZIP:12201
Country:US
Phone:518-434-3147
CAGE:KO822

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ACETATE (SARA III)
CAS:141-78-6
RTECS

#:AH5425000
Fraction by Wt: 85.0%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 15.0%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,MUCOUS
MEMBRANES AND RESPIRATORY TRACT (MODERATELY TOXIC
) . CHRONIC:NO DATA
AVAILABLE.
Explanation of Carcinogenicity:NO DATA AVAILABLE.
Effects of Overexposure:SEE HEALTH HAZARDS DATA.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. EYE:FLUSH WITH PLENTY OF
WATER FOR ABOUT 15 MINUTES;CALL A PHYSICIAN IMMEDIATELY. SKIN:WASH
THOROUGHLY WITH SOAP AND WATER.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:27F/-2.8C
Lower
Limits:2.05
Upper Limits:9.3
Extinguishing Media:WATER SPRAY,DRY CHEMICAL,CO*2.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID;USE REASONABLE CARE.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE
LIQUID IF POSSIBLE;USE SUITABLE INERT ABSORBENT MATERIAL AND
RECOVER FOR PROPER DISPOSAL.

===== Handling and

Storage =====

Handling and Storage Precautions:STORE IN COOL/DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT,OPEN FLAMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE PEL/TLV.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:IMPERVIOUS.

Eye Protection:SAFETY GOGGLES/GLASSES.

Other Protective Equipment:PROTECTIVE CLOTHING/EYE-WASH FACILIT IES.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS/MIST.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=72.C, 161.6F

Vapor Pres:77

Vapor Density:3.0

Spec Gravity:0.8945

Evaporation Rate & Reference:4.2 (NO REF GIVEN)

Solubility in Water:SLIGHT

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:

YES

OXIDIZING MATERIALS.

Stability Condition to Avoid:EXTREME HEAT.

Hazardous Decomposition Products:CO OR CO*2.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL OR INCINERATION MUST BE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner wh

atsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.