

3M COMPANY - ADHESIVES COATINGS, SEALERS DIV -- SCOTCHWELD 3500B CORE SPLICE
ADHESIVE,PT B -- 8030-00-145-0534

===== Product Identification =====

Product ID:SCOTCHWELD 3500B CORE SPLICE ADHESIVE,PT B

MSDS Date:01/01/1988

FSC:8030

NIIN:00-145-0534

Kit Part:Y

MSDS Number: BGVQD

=== Responsible Party ===

Company Name:3M COMPANY - ADHESIVES COATINGS, SEALERS DIV

Address:3M CENTER

City:ST PAUL

State:M

N

ZIP:55144-1000

Country:US

Info Phone Num:SAME

Emergency Phone Num:612-733-1110

CAGE:04963

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN

CAS:5026-74-4

Fraction by Wt: 60-70%

Ingred Name:CLAY

CAS:68953-58-2

Fraction by Wt: 1-10

%
Fraction by Wt: 20-30%

=====
Hazards Identification
=====

LD50 LC50 Mixture:NOT GIVEN
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:IRRITANT, ALLERGEN,
Effects of Overexposure:EYE: IRRITATION POSSIBLE. SKIN: IRRITATION AND
POSSIBLE ALLERGIC REACTIONS. INHALATION: IRRITATION OF UPPER
RESPIRATORY TRACT. INGESTION: IRRITATION OF GI TRACT. DUST FROM
FABRICA
TION MAY IRRITATE ANY O RGAN EXPOSED.
Medical Cond Aggravated by Exposure:ANY PREEXISTING ALLERGY,
SENSITIVITY OR ORGAN DYSFUNCTION.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH 10 MINUTES W/AMPLE WATER. SKIN: WASH WITH SOAP:
WATER, INHALATION; REMOVE TO FRESH AIR. GIVE OXYGEN OR ART
RESPIRATION AS REQUIRED, INGESTION: DO NOT INDUCE VOMITING. IF
CONSCIOUS, GIVE TWO GLASSES MILK OR WATER, CALL PHYSICIAN PROMPTLY
ALL EXPOSURES IF
PROLONGED OR SEVERE.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICALS
Fire Fighting Procedures:USE SCBA WHILE FIGHTING FIRES INVOLVING THIS
MATERIAL.
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:OBSERVE ALL PRECAUTIONS GIVEN. COLLECT SPILL
BY WIPING OR WITH ABSORBENT AS REQUIRED, PLACE IN CLOSABLE
CONTAINER

=====
Handling and Storage
=====

Handling and Storage Precautions:USE W/ADEQUATE VENTILATION ONLY. KEEP
CONTAINER CLOSED.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE GIVEN
Ventilation:USE ONLY W/SUFFICIENT VENTILATION TO PREVENT VAPOR BUILDUP.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES, CHEMICAL GOGGLES.
Work Hygienic Practices:AVOID EYE-SKIN CONTACT. DO NOT INHALE OR
INGEST, VAPO

R OR DUST FROM FABRICATION.LAUNDER CONTAMINATED
CLOTHING BEFORE USE
Supplemental Safety and Health
ENTRY PER 3M MSDS DOC#10-9703-9 DATED 16JAN89, 3M GENERIC ID IS
62-3500-XXXX-X, PART B OF TWO-PART B/A KIT.

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity:0.65
Solubility in Water:VERY SLIGHT
Appearance and Odor:TAN PASTE WITH PUNGENT ODOR.
Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stabilit
y Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CARBON OXIDES, SMOKE PARTICLES

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR LANDFILL IAW ALL LAWS & REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or
implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.