

DEXTER HYSOL/AEROSPACE & INDUSTRIAL PRODUCTS DIV. -- EA 9309.3NA PART A --
8040-01-163-3481

===== Product Identification =====

Product ID:EA 9309.3NA PART A

MSDS Date:03/11/1987

FSC:8040

NIIN:01-163-3481

Kit Part:Y

MSDS Number: BGWFW

=== Responsible Party ===

Company Name:DEXTER HYSOL/AEROSPACE & INDUSTRIAL PRODUCTS DIV.

Address:2850 WILLOW PASS ROAD

Box:312

City:PITTSBURG

State:CA

ZIP:94565

Coun

try:US

Info Phone Num:415-687-4201

CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN SYSTEM

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:SILICA, AMORPHOUS, DUST

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 3

00F/148.9C

Extinguishing Media: DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER SPRAY, FOAM OR FOG.

Fire Fighting Procedures: USE SELF CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard: DENSE SMOKE & TOXIC GASES MAY BE LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures: WEAR PROTECTIVE CLOTHING, GLOVES & SAFETY GLASSES. SCRAPE UP & TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE W/ SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP COOL IN ACCORDANCE W/ LABEL INSTRUCTIONS. AVOID MIXING RESIN & CURING AGENT IN BATCHES GREATER THAN 1 POUND TOTAL. STORE @ RM TEMP(77F) FOR 12MO

Other Precautions: FOLLOW RECOMMENDED CURING SCHEDULE. DON'T HEAT MIXED ADHESIVE ABOVE 75F UNLESS CURING SURFACES TO BE BONDED. FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD-UP W/ THE RELEASE OF TOXIC GASES!

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NOT NEEDED W/ GOOD INDUSTRIAL VENTILATION; ORGANIC CARTRIDGE RESPIRATOR.

Ventilation: LOCAL EXHAUST RECOMMENDED.

Protective Gloves: IMPERVIOUS PLASTIC OR RUBBER.

Eye Protection: SAFETY GLASSES OR GOGGLES.

Other Protective Equipment: AS NEEDED TO PROTECT SKIN & CLOTHING.

Work Hygienic Practices: WASH THOROUGHLY AFTER USE & BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: C3

Boiling Pt: B.P. Text: DECOMPOSES

Vapor Pres: 1.

Evaporation Rate & Reference: NIL

Solubility in Water: NIL

Appearance and Odor: VISCOUS PINK PASTE W/ SLIGHT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:OXIDES OF CARBON, NITROGEN, ALDEHYDES,
ACIDS & UNDETERMINED ORGANICS.

Conditions to Avoid Polymerization:AVOID MIXING RESIN & CURING AGENT IN
BATCHES GREATER THAN 1 LB.DONOT HEAT MIXED ADHESIVE ABOVE 75F
UNLESS CURING BOND.SF

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO DOT
HAZARD CLASS. IF NOT REGULATED BY DOT, DISPOSE OF AS ORM-E.

Disclaimer (provided w

ith this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.