

GENERAL ELECTRIC CO. -- RTV9950 -- 8040-00-116-4337

===== Product Identification =====

Product ID:RTV9950
MSDS Date:10/25/1988
FSC:8040
NIIN:00-116-4337
MSDS Number: BGZXZ
=== Responsible Party ===
Company Name:GENERAL ELECTRIC CO.
City:WATERFORD
State:NY
ZIP:12188
Info Phone Num:(518) 237-3330
Emergency Phone Num:(518) 237-3330
CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL EL
ECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT
Address:260 HUDSON RIVER RD
Box:City:WATERFORD
State:NY
ZIP:12188
Country:US
Phone:518-237-3330/800-332-3390
CAGE:01139

===== Composition/Information on Ingredients =====

Ingred Name:DIBUTYL TIN DILAURATE (AS TIN)
CAS:77-58-7
RTECS #:WH7000000
Fraction by Wt: 5-10%
Other REC Limits:0.1 MG/CUM (SN)
OSHA PEL:S, 0.1 MG/M3
ACGIH TLV:S, 0.1 MG/M3; 8990

Ingred Name:NON-HAZARDOUS FOR INGREDIENTS

===== Hazards Identificati

on =====

LD50 LC50 Mixture:ORAL LD50 175MG/KG (RAT)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: CAUSES MODERATE IRRITATION.

INHALATION: CAUSES MODERATE RESPIRATORY IRRITATION, CNS DAMAGE & RESPIRATORY AILMENTS. EYE: CAUSES SEVERE IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: CAUSES MODERATE IRRITATION. INHALATION: CAUSES MODERATE R

ESPIRATORY IRRITATION, CNS DAMAGE & RESPIRATORY AILMENTS. EYE:CAUSES SEVERE IRRITATION.

Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS, CNS DISORDERS.

===== First Aid Measures =====

First Aid:INGESTION: INDUCE VOMITING BY GIVING 2 GLASSES OF WATER/STICKING FINGERS DOWN THROAT; NEVER GIVE ANYTHING TO AN UNCONSCIOUS PERSON. GET MED ATT. SKIN: REMOVE CONTAMINATED CLOTHING/LAUNDER BEFORE REUSE . WASH W/SOAP & WATER. REMOVE CON

TAMINATED SHOES/DISCARD. GET MED ATT IF IRRITATION PERSISTS.

INHALATION: MOVE PERSON TO FRESH AIR. EYE: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. GET MED ATT.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:>200F

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE/SOAK UP IN AN INERT MATERIAL & PUT IN A CONTAINER

FOR DISPOSAL. WASH WALKING SURFACES W/DETERGENT

& WATER TO REDUCE SLIPPING HAZARD. WARN OTHER WORKERS OF SPILL. INCREASE AREA VENTILATION .

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID BREATHING VAPORS. AVOID CONTACT W/SKIN & EYES. REMOVE CONTAMINATED CLOTHING & SHOES/LAUNDER BEFORE REUSE.

Other Precautions:USE ONLY IN A WELL VENTILATED AREA. KEEP AWAY FROM FOOD/SMOKING MAT

ERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE IN A WELL VENTILATED AREA. USE APPROVED
NIOSH RESPIRATORY PROTECTION IF TLV EXCEEDED.

Ventilation:USE ONLY IN WELL VENTILATED AREA. MECHANICAL.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES, MONOGOGGLES.

Other Protective Equipment:APRON, EYE PROTECTION/PROTECTIVE CLOTHING.
SHOWERS/EYEBATH.

Work Hygienic Practices:WASH HANDS BEFORE EATING & SMOKING. REMOVE
CONTAMINATED CLO

THING & SHOES/LAUNDER BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>250F

Spec Gravity: 1.67

Evaporation Rate & Reference:(BU AC = 1):